

QUARTZCOLOR 2015

| Nr Kat. | Artykuł | Cena brutto |
|---------|---------|-------------|
| | | z VAT -em |
| | | [ZŁ] * |


LED

QuartzColor LED Fresnels

| | | |
|----------|--|-----------|
| LD27630T | Studio LED Fresnel 40W Tungsten MO Head fitted w/ Fresnel lens Ø130mm, 5m length bare ended cable, in-line switch, built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | 7 846 zł |
| LD27631T | Studio LED Fresnel 40W Tungsten PO Head fitted w/ Fresnel lens Ø130mm, 2m length bare ended cable (no switch), built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | 8 853 zł |
| LD27630D | Studio LED Fresnel 40W Daylight MO Head fitted w/ Fresnel lens Ø130mm, 5m length bare ended cable, in-line switch, built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | 7 846 zł |
| LD27631D | Studio LED Fresnel 40W Daylight PO Head fitted w/ Fresnel lens Ø130mm, 2m length bare ended cable (no switch), built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | 8 853 zł |
| | Additional | |
| 28047 | Gel frame Ø168mm | 137 zł |
| 28309 | Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm) | 314 zł |
| 28049 | Cone w/ variable aperture Ø168mm | 533 zł |
| 28106 | manual "L"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket | 170 zł |
| 28048 | 4-leaf rotating barndoor Ø168mm | 373 zł |
| 28837 | 8-leaf rotating barndoor Ø168mm | 687 zł |
| 82012P | Small C-clamp w/ 16mm (5/8") spigot | 162 zł |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) | 88 zł |
| LD27640T | Studio LED Fresnel 90W Tungsten MO Head fitted w/ Fresnel lens Ø130mm, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | 10 062 zł |



| | | |
|---|---|-----------|
| LD27642T | Studio LED Fresnel 90W Tungsten PO | 10 451 zł |
| | Head fitted w/ Fresnel lens Ø130mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1½") spigot | |
| | Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | |
| LD27640T/1 | Retrofit kit 90W Tungsten for Bambino1KW | 7 644 zł |
| | Base composed w/ 90W tungsten led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors | |
| | Supplied w/ upgrade label kit | |
| LD27640D | Studio LED Fresnel 90W Daylight MO | 10 062 zł |
|  | Head fitted w/ Fresnel lens Ø130mm, 5m length bare ended cable, in-line <u>switch</u> , built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1½") spigot | |
| | Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | |
| LD27642D | Studio LED Fresnel 90W Daylight PO | 10 451 zł |
| | Head fitted w/ Fresnel lens Ø130mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1½") spigot | |
| | Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | |
| LD27640D/1 | Retrofit kit 90W Daylight for Bambino1KW | 7 644 zł |
|  | Base composed w/ 90W daylight led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors | |
| | Supplied w/ upgrade label kit | |
| | Additional | |
| 28849 | Gel frame Ø198mm | 158 zł |
| 28844 | Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm) | 357 zł |
| 28840 | Cone w/ variable aperture Ø200mm | 687 zł |
| 28846 | 4-leaf rotating barndoor Ø200mm | 417 zł |
| 28847 | 8-leaf rotating barndoor Ø200mm | 634 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) | 88 zł |
| LD27250T | Studio LED Fresnel 120W Tungsten MO | 11 224 zł |
|  | Head fitted w/ Fresnel lens Ø175mm, 5m length bare ended cable, in-line <u>switch</u> , built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1½") spigot | |
| | Supplied w/ stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm | |
| LD27252T | Studio LED Fresnel 120W Tungsten PO | 11 612 zł |
| | Head fitted w/ Fresnel lens Ø175mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1½") spigot | |
| | Supplied w/ stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm | |
| LD27252T/1 | Retrofit kit 120W Tungsten for Studio1KW | 7 980 zł |
|  | Base composed w/ 120W tungsten led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors | |
| | Supplied w/ upgrade label kit | |

| | | |
|---|--|-----------|
| LD27250D | Studio LED Fresnel 120W Daylight MO | 11 224 zł |
|  | <p>Head fitted w/ Fresnel lens Ø175mm, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot</p> <p>Supplied w/ stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm</p> | |
| LD27252D | Studio LED Fresnel 120W Daylight PO | 11 612 zł |
| | <p>Head fitted w/ Fresnel lens Ø175mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot</p> <p>Supplied w/ stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm</p> | |
| LD27252D/1 | Retrofit kit 120W Daylight for Studio1KW | 7 980 zł |
|  | <p>Base composed w/ 120W daylight led source, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors</p> <p>Supplied w/ upgrade label kit</p> | |
| | Additional | |
| 28859 | Gel frame Ø258mm | 170 zł |
| 28304 | Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm) | 506 zł |
| 28850 | Cone w/ variable aperture Ø269mm | 714 zł |
| 28050 | 4-leaf rotating barndoor Ø269mm | 426 zł |
| 28857 | 8-leaf rotating barndoor Ø269mm | 751 zł |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| 28151 | Accessory safety bond (Ø2mm, length 50cm) | 88 zł |
| LD27260T | Studio LED Fresnel 200W Tungsten MO | 0 zł |
|  | <p>Head fitted w/ Fresnel lens Ø250mm, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot</p> <p>Supplied w/ stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p> | |
| LD27262T | Studio LED Fresnel 200W Tungsten PO | 0 zł |
| | <p>Head fitted w/ Fresnel lens Ø250mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot</p> <p>Supplied w/ stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p> | |
| LD27262T/1 | Retrofit kit 200W Tungsten for Studio 2KW | 0 zł |
| | <p>Base composed w/ 200W tungsten led source, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors</p> <p>Supplied w/ upgrade label kit</p> | |
| LD27260D | Studio LED Fresnel 200W Daylight MO | 0 zł |
|  | <p>Head fitted w/ Fresnel lens Ø250mm, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot</p> <p>Supplied w/ stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p> | |
| LD27262D | Studio LED Fresnel 200W Daylight PO | 0 zł |
| | <p>Head fitted w/ Fresnel lens Ø250mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot</p> <p>Supplied w/ stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p> | |

LD27262D/1

Retrofit kit 200W Daylight for Studio 2KW

0 zł



Base composed w/ 200W daylight led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors

Supplied w/ upgrade label kit

Additional

| | | |
|-------|--|--------|
| 28093 | Gel frame Ø323mm | 224 zł |
| 28306 | Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm) | 571 zł |
| 28090 | Cone small aperture Ø323mm | 400 zł |
| 28091 | Cone medium aperture Ø323mm | 400 zł |
| 28092 | Cone large aperture Ø323mm | 400 zł |
| 28070 | 4-leaf rotating barndoor Ø323mm | 586 zł |
| 28071 | 8-leaf rotating barndoor Ø323mm | 836 zł |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| 28150 | Accessory safety bond (Ø2mm, length 70cm) | 88 zł |

Open face floodlights**QuartzColor Pinza**

| | | |
|-------|---------------------------------------|--------|
| 21010 | Pinza 500W floodlight 230-240V | 712 zł |
|-------|---------------------------------------|--------|

Head fitted w/ On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

Supplied w/ clamp on flexible arm

| | | |
|-------|---|--|
| 21012 | Black Pinza 500W floodlight 230-240V | |
|-------|---|--|

Head fitted w/ black painted housing, On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

Supplied w/ clamp on flexible arm

| | | |
|-------|---|----------|
| 21011 | Pinza 500W floodlight 230-240V w/ barndoor | 1 199 zł |
|-------|---|----------|

Head fitted w/ On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

Supplied w/ direct mount complete barndoor set + clamp on flexible arm

| | | |
|-------|---|----------|
| 21013 | Black Pinza 500W floodlight 230-240V w/ barndoor | 1 199 zł |
|-------|---|----------|

Head fitted w/ black painted housing, On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

Supplied w/ direct mount complete barndoor set + clamp on flexible arm

Additional

Incandescent (Argaphoto) lamp type P2/1 500W 230V (E27 base) 3200K

Incandescent (Argaphoto) lamp type P2/1 500W 240V (E27 base) 3200K

| | | |
|-------|--|--------|
| 28023 | Direct mount wire mesh safety guard 3 x 3mm Ø166mm | 192 zł |
| 28021 | Accessory holder Ø192mm | 318 zł |
| 28019 | Wire mesh safety guard 3 x 3mm (to be used w/ 28021) | 121 zł |
| 28302 | Scrim set 4 pieces (full single + full double + half single + half double; Ø192mm) | 357 zł |
| 28122 | Barndoor adapter w/ wire mesh safety guard 3 x 3mm | 230 zł |
| 28022 | 4-leaf barndoor Ø164mm (to be used w/ 28021 or 28122) | 318 zł |
| 28120 | Direct mount complete barndoor set (28122 + 28022) | 450 zł |

QuartzColor Redhead

For Redheads kits, see separate price list



| | | |
|-------|---|----------|
| 27157 | Redhead 800W variable beam floodlight 230-240V | 1 172 zł |
|-------|---|----------|

Head fitted w/ On/Off in-line rocker switch 10A/250V, 4m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket

Supplied w/ rotating barndoor adapter w/ wire mesh safety guard 3 x 3mm + 4-leaf barndoor Ø164mm

| | | |
|-------|---|----------|
| 27130 | Redhead 800W variable beam floodlight 230-240V w/ accessory holder | 1 412 zł |
|-------|---|----------|

Head fitted w/ On/Off in-line toggle switch 10A/250V, 4m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket

Supplied w/ rotating accessory holder Ø192mm + wire mesh safety guard 3 x 3mm + 4-leaf barndoor Ø164mm

| | | |
|-------------------------------|---|----------|
| 27158 | Redhead 1000W variable beam floodlight 230-240V Head fitted w/ On/Off in-line toggle switch 10A/250V, 4m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket Supplied w/ barndoor adapter w/ wire mesh safety guard 3 x 3mm + 4-leaf barndoor Ø164mm | 1 199 zł |
| Additional for Redhead | | |
| | Tungsten halogen DE linear lamp type P2/13 (DXX) 800W 230V (R7s base, MOL 79.4mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/13 (DXX) 800W 240V (R7s base, MOL 79.4mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/35 1000W 230V (R7s base, MOL 95.3mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/35 1000W 240V (R7s base, MOL 95.3mm) 3200K | |
| 28023 | Direct mount wire mesh safety guard 3 x 3mm Ø166mm | 192 zł |
| 28021 | Rotating accessory holder Ø192mm | 318 zł |
| 28019 | Wire mesh safety guard 3 x 3mm (to be used w/ 28021) | 121 zł |
| 28024 | Mounted safety glass Ø192mm (to be used w/ 28021) | 148 zł |
| 28025 | Mounted Dichroic filter Ø192mm (to be used w/ 28021) | 724 zł |
| 28122 | Rotating barndoor adapter w/ wire mesh safety guard 3 x 3mm | 230 zł |
| 28022 | 4-leaf barndoor Ø164mm (to be used w/ 28021 or 28122) | 318 zł |
| 28120 | Direct mount complete barndoor set (28122 + 28022) | 450 zł |
| 28302 | Scrim set 4 pieces (full single + full double + half single + half double; Ø192mm) | 357 zł |
| 28602 | Softbox V+ (40 x 55 cm), to be used w/ 28600 | 1 468 zł |
| 28600 | Mounting device for softbox V+ 40 x 55 cm (for 28602) | 780 zł |
| 28603 | Softbox V+ (40 x 55 cm) + Redhead mounting device (28602 + 28600) | 2 248 zł |
| 82610 | Small clamp w/ 16mm (5/8") spigot | 112 zł |





QuartzColor Blonde







For Blonde kits, see separate price list

| | | |
|------------------------------------|---|----------|
| 21100 | Blonde 2000W variable beam floodlight 230-240V Head fitted w/ On/Off in-line toggle switch 20A/250V, 5.5m length bare ended cable, integrated accessory holder, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted Supplied w/ wire mesh safety guard 3 x 3mm + 4-leaf rotating barndoor Ø269mm | 2 477 zł |
| 21101 | Black Blonde 2000W variable beam floodlight 230-240V Head fitted w/ black painted housing, On/Off in-line toggle switch 20A/250V, 5.5m length bare ended cable, integrated accessory holder, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted Supplied w/ wire mesh safety guard 3 x 3mm + 4-leaf rotating barndoor Ø269mm | 2 583 zł |
| Additional for Black Blonde | | |
| | Tungsten halogen DE linear lamp type P2/27 (FEX) 2000W 230V (R7s base, MOL 143.8mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/27 (FEX) 2000W 240V (R7s base, MOL 143.8mm) 3200K | |
| 28051 | Direct mount wire mesh safety guard 3 x 3mm Ø253.6mm | 247 zł |
| 28304 | Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm) | 506 zł |
| 28053 | Mounted safety glass Ø258mm | 379 zł |
| 28054 | Mounted Dichroic filter Ø258mm | 1 369 zł |
| 28050 | 4-leaf rotating barndoor Ø269mm | 426 zł |
| 28612 | Softbox V+ (90 x 120 cm) w/ 3 front diffuser screens | 3 536 zł |
| 28610 | Ring Ø270mm (for 28612) | 1 904 zł |
| 28613 | Softbox V+ (90 x 120 cm) + ring Ø270mm (28612 + 28610) | 5 440 zł |
| 82610 | Small clamp w/ 16mm (5/8") spigot | 112 zł |
| 82012P | Small C-clamp w/ 16mm (5/8") spigot | 162 zł |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) | 88 zł |

Tungsten spotlights QuartzColor Bambino Fresnels

For Bambino kits (500/300 & 650/500W), see separate price list



| | | |
|---|---|----------|
| 27620 | Bambino Fresnel 500/300W MO 230-240V w/ "U"-shape stirrup | 1 918 zł |
|  | Head fitted w/ Proprietary Fresnel lens Ø90mm, On/Off in-line rocker switch 10A/250V, 4m length bare ended cable and manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted Supplied w/ gel frame Ø110mm + 4-leaf rotating barndoor Ø110mm | |
| Additional | | |
| | Tungsten halogen SE lamp type CP81 (FMF) 300W 230V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP81 (FSK) 300W 240V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP82 (FRH) 500W 230V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP82 (FRJ) 500W 240V (GY9.5 base, oriented 2-pin) 3200K | |
| 28080 | Gel frame Ø110mm (not for 120V products) | 80 zł |
| 28301 | Scrim set 4 pieces (full single + full double + half single + half double; Ø110mm) | 256 zł |
| 28104 | Cone w/ variable aperture Ø110mm | 309 zł |
| 28105 | manual "L"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket | 160 zł |
| 28040 | 4-leaf rotating barndoor Ø110mm (not for 120V products) | 240 zł |
| 82012P | Small C-clamp w/ 16mm (5/8") spigot | 162 zł |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) | 88 zł |
| 27630 | Bambino Fresnel 650/500W MO 230-240V w/ "U"-shape stirrup | 2 237 zł |
|  | Head fitted w/ Fresnel lens Ø130mm, On/Off in-line rocker switch 10A/250V, 4m length bare ended cable and manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted Supplied w/ gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm | |
| 27631 | Bambino Fresnel 650/500W PO 230-240V | 3 622 zł |
| | Head fitted w/ Fresnel lens Ø130mm, On/Off head mounted toggle switch 8A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm | |
| Additional | | |
| | Tungsten halogen SE lamp type CP81 (FMF) 300W 230V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP81 (FSK) 300W 240V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP82 (FRH) 500W 230V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP82 (FRJ) 500W 240V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP89 (FRL) 650W 230V (GY9.5 base, oriented 2-pin) 3200K | |
| | Tungsten halogen SE lamp type CP89 (FRM) 650W 240V (GY9.5 base, oriented 2-pin) 3200K | |
| 28047 | Gel frame Ø168mm | 137 zł |
| 28309 | Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm) | 314 zł |
| 28049 | Cone w/ variable aperture Ø168mm | 533 zł |
| 28106 | manual "L"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket | 170 zł |
| 28048 | 4-leaf rotating barndoor Ø168mm | 373 zł |
| 28837 | 8-leaf rotating barndoor Ø168mm | 687 zł |
| 82012P | Small C-clamp w/ 16mm (5/8") spigot | 162 zł |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) | 88 zł |
| 27640 | Bambino Fresnel 1kW MO Mk2 230-240V | 3 047 zł |
|  | Head fitted w/ Fresnel lens Ø130mm, On/Off in-line rocker switch 15A/250V, 5m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | |
| 27642 | Bambino Fresnel 1kW PO Mk2 230-240V | 4 075 zł |
|  | Head fitted w/ Fresnel lens Ø130mm, On/Off head mounted toggle switch 8A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm | |
| Additional | | |
| | Tungsten halogen SE lamp type CP40 (FKJ) 1000W 230V (G22 base, medium bi-post) 3200K | |
| | Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K | |

| | | |
|---|---|-----------------|
| 28849 | Gel frame Ø198mm | 158 zł |
| 28844 | Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm) | 357 zł |
| 28840 | Cone w/ variable aperture Ø200mm | 687 zł |
| 28846 | 4-leaf rotating barndoor Ø200mm | 417 zł |
| 28847 | 8-leaf rotating barndoor Ø200mm | 634 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) | 88 zł |
| <hr/> | | |
|  | 27650 Bambino Fresnel 2kW MO Mk2 230-240V Head fitted w/ Fresnel lens Ø175mm, On/Off <u>head mounted</u> toggle switch 20A/250V, 5m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spigot Supplied w/ gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm | 3 995 zł |
| <hr/> | | |
|  | 27652 Bambino Fresnel 2kW PO Mk2 230-240V Head fitted w/ Fresnel lens Ø175mm, On/Off <u>head mounted</u> toggle switch 20A/250V, 2m length bare ended cable, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spigot Supplied w/ gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm | 4 794 zł |
| <hr/> | | |
| Additionalis | | |
| Tungsten halogen SE lamp type CP41 (FKK) 2000W 230V (G38 base, mogul bi-post) 3200K | | |
| Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K | | |
| <hr/> | | |
| 28859 | Gel frame Ø258mm | 170 zł |
| 28304 | Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm) | 506 zł |
| 28850 | Cone w/ variable aperture Ø269mm | 714 zł |
| 28050 | 4-leaf rotating barndoor Ø269mm | 426 zł |
| 28857 | 8-leaf rotating barndoor Ø269mm | 751 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |
| 28151 | Accessory safety bond (Ø2mm, length 50cm) | 88 zł |
| <hr/> | | |
|  | 27660 Bambino Fresnel 5kW MO Mk2 230-240V Head fitted w/ Fresnel lens Ø250mm, On/Off <u>head mounted</u> toggle switch 60A/250V, 5m length bare ended cable and manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm | 5 566 zł |
| <hr/> | | |
|  | 27662 Bambino Fresnel 5kW PO Mk2 230-240V Head fitted w/ Fresnel lens Ø250mm, On/Off <u>head mounted</u> toggle switch 60A/250V, 2m length bare ended cable, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) stirrup w/ 28mm (1½") spigot Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm | 6 232 zł |
| <hr/> | | |
| Additionalis | | |
| Tungsten halogen SE lamp type CP29 5000W 230V (G38 base, mogul bi-post) 3200K | | |
| Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K | | |
| <hr/> | | |
| 28093 | Gel frame Ø323mm | 224 zł |
| 28306 | Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm) | 571 zł |
| 28090 | Cone small aperture Ø323mm | 400 zł |
| 28091 | Cone medium aperture Ø323mm | 400 zł |
| 28092 | Cone large aperture Ø323mm | 400 zł |
| 28070 | 4-leaf rotating barndoor Ø323mm | 586 zł |
| 28071 | 8-leaf rotating barndoor Ø323mm | 836 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |
| 28150 | Accessory safety bond (Ø2mm, length 70cm) | 88 zł |
| <hr/> | | |
|  | 27680 Bambino Fresnel 10kW MO Mk2 230-240V Head fitted w/ Fresnel lens Ø350mm, On/Off <u>head mounted</u> rotary switch 125A/250V, 5m length bare ended cable and manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot Supplied w/ gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm | 0 zł |
| <hr/> | | |
|  | 27682 Bambino Fresnel 10kW PO Mk2 230-240V Head fitted w/ Fresnel lens Ø350mm, On/Off <u>head mounted</u> rotary switch 125A/250V, 2m length bare ended cable, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spigot Supplied w/ gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm | 0 zł |
| <hr/> | | |
| Additionalis | | |
| Tungsten halogen SE lamp type CP83 10000W 230V (G38 base, mogul bi-post) 3200K | | |
| Tungsten halogen SE lamp type CP83 10000W 240V (G38 base, mogul bi-post) 3200K | | |

| | | |
|-------|--|--------|
| 28097 | Gel frame Ø408mm | 250 zł |
| 28307 | Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm) | 818 zł |
| 28094 | Cone small aperture Ø401mm | 618 zł |
| 28095 | Cone small medium Ø401mm | 618 zł |
| 28096 | Cone large aperture Ø401mm | 618 zł |
| 28074 | 4-leaf rotating barndoor Ø401mm | 664 zł |
| 28075 | 8-leaf rotating barndoor Ø401mm | 879 zł |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) | 277 zł |

QuartzColor Studio Fresnels

| | | | |
|---|---------|---|----------|
|  | 27250 | Studio Fresnel 1kW MO Mk2 230-240V Head fitted w/ Fresnel lens Ø175mm, On/Off head mounted toggle switch 8A/250V, 5m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1 1/8") socket Supplied w/ gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm | 3 356 zł |
| | 27250S1 | Special version w/o switch , 2m length bare ended cable | 3 249 zł |
|  | 27252 | Studio Fresnel 1kW PO Mk2 230-240V Head fitted w/ Fresnel lens Ø175mm, On/Off head mounted toggle switch 80A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") socket Supplied w/ gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm | 4 315 zł |
| | 27252S1 | Special version w/o switch , 2m length bare ended cable | 4 208 zł |
| | | Additional | |
| | | Tungsten halogen SE lamp type CP40 (FKJ) 1000W 230V (G22 base, medium bi-post) 3200K | |
| | | Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K | |
| | 28859 | Gel frame Ø258mm | 170 zł |
| | 28304 | Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm) | 506 zł |
| | 28850 | Cone w/ variable aperture Ø269mm | 714 zł |
| | 28050 | 4-leaf rotating barndoor Ø269mm | 426 zł |
| | 28857 | 8-leaf rotating barndoor Ø269mm | 751 zł |
| | 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| | 28151 | Accessory safety bond (Ø2mm, length 50cm) | 88 zł |
|  | 27260 | Studio Fresnel 2kW MO Mk2 230-240V Head fitted w/ Fresnel lens Ø250mm, On/Off head mounted toggle switch 16A/250V, 5m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and 28mm (1 1/8") socket Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm | 4 821 zł |
| | 27260S1 | Special version w/o switch , 2m length bare ended cable | 4 688 zł |
|  | 27262 | Studio Fresnel 2kW PO Mk2 230-240V Head fitted w/ Fresnel lens Ø250mm, On/Off head mounted toggle switch 16A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") socket Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm | 5 716 zł |
| | 27262S1 | Special version w/o switch , 2m length bare ended cable | 5 471 zł |
| | 27262S2 | Special version with On/Off head mounted rotary switch 16A/250V , 2m length bare ended cable | 5 966 zł |
| | | Additional | |
| | | Tungsten halogen SE lamp type CP41 (FKK) 2000W 230V (G38 base, mogul bi-post) 3200K | |
| | | Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K | |
| | 28093 | Gel frame Ø323mm | 224 zł |
| | 28306 | Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm) | 571 zł |
| | 28090 | Cone small aperture Ø323mm | 400 zł |
| | 28091 | Cone medium aperture Ø323mm | 400 zł |
| | 28092 | Cone large aperture Ø323mm | 400 zł |
| | 28070 | 4-leaf rotating barndoor Ø323mm | 586 zł |
| | 28071 | 8-leaf rotating barndoor Ø323mm | 836 zł |
| | 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| | 28150 | Accessory safety bond (Ø2mm, length 70cm) | 88 zł |

| | | | |
|---|---------|---|--------|
|  | 27270 | Studio Fresnel 5kW MO Mk2 230-240V Head fitted w/ Fresnel lens Ø300mm, On/Off head mounted rotary switch 45A/250V, 5m length bare ended cable, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm | 0 zł |
| | 27270S1 | Special version w/o switch , 2m length bare ended cable | 0 zł |
|  | 27272 | Studio Fresnel 5kW PO Mk2 230-240V Head fitted w/ Fresnel lens Ø300mm, On/Off head mounted rotary switch 45A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm | 0 zł |
| | 27272S1 | Special version w/o switch , 2m length bare ended cable | 0 zł |
| | | Additional Tungsten halogen SE lamp type CP29 5000W 230V (G38 base, mogul bi-post) 3200K Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K | |
| | 28097 | Gel frame Ø408mm | 250 zł |
| | 28307 | Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm) | 818 zł |
| | 28094 | Cone small aperture Ø401mm | 618 zł |
| | 28095 | Cone small medium Ø401mm | 618 zł |
| | 28096 | Cone large aperture Ø401mm | 618 zł |
| | 28074 | 4-leaf rotating barndoor Ø401mm | 664 zł |
| | 28075 | 8-leaf rotating barndoor Ø401mm | 879 zł |
| | 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| | 82002 | Safety cable 50kg (Ø4mm, length 70cm) | 277 zł |

QuartzColor Tungsten Pars

| | | | |
|--|-------|---|----------|
| | 27940 | Tungsten Par 1kW MO 230-240V w/o switch Head fitted w/ 7m length bare ended cable (no switch), full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot | 0 zł |
| | 27941 | Tungsten Par 1kW MO 230-240V Head fitted w/ On/Off in-line toggle switch 15A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm | 0 zł |
| | | Additional Tungsten halogen SE lamp type CP40 (FKJ) 1000W 230V (G22 base, medium bi-post) 3200K Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K | |
| | 28093 | Gel frame Ø323mm | 224 zł |
| | 28306 | Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm) | 571 zł |
| | 28114 | 4-leaf rotating barndoor Ø323mm | 510 zł |
| | 28071 | 8-leaf rotating barndoor Ø323mm | 836 zł |
| | 28341 | Mounted spot lens Ø250mm, black handle | 932 zł |
| | 28342 | Mounted medium flood lens Ø250mm, green handle | 932 zł |
| | 28343 | Mounted wide flood lens Ø250mm, yellow handle | 932 zł |
| | 28344 | Mounted extra-wide flood lens Ø250mm, red handle | 932 zł |
| | 28345 | Mounted frosted Fresnel lens Ø250mm, white handle | 879 zł |
| | 28848 | Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel: Ø250mm) | 4 384 zł |
| | 28814 | Carrying case for 5 lenses Ø250mm (for HMI Par 1.2kW, OneLight™ HMI Par 1.2kW & Tungsten Par 1kW); 38 x 43 x 42cm (ext. dim. L x W x H) weight (empty) 7kg | |
| | 28806 | Complete diffusion lens set Ø250mm w/ carrying case (28848 + 28814) | 5 832 zł |
| | 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| | 82002 | Safety cable 50kg (Ø4mm, length 70cm) | 277 zł |
| | 27950 | Tungsten Par 2kW MO 230-240V w/o switch Head fitted w/ 7m length bare ended cable (no switch), full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot | 0 zł |
| | 27951 | Tungsten Par 2kW MO 230-240V Head fitted w/ On/Off in-line toggle switch 20A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ gel frame Ø400mm + 4-leaf rotating barndoor Ø401mm | 0 zł |

Additional

Tungsten halogen SE lamp type CP41 (FKK) 2000W 230V (G38 base, mogul bi-post) 3200K

Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K

| | | |
|-------|---|----------|
| 28097 | Gel frame Ø408mm | 250 zł |
| 28307 | Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm) | 818 zł |
| 28115 | 4-leaf rotating barndoor Ø401mm | 647 zł |
| 28075 | 8-leaf rotating barndoor Ø401mm | 879 zł |
| 28441 | Mounted spot lens Ø350mm, black handle | 1 604 zł |
| 28442 | Mounted medium flood lens Ø350mm, green handle | 1 604 zł |
| 28443 | Mounted wide flood lens Ø350mm, yellow handle | 1 604 zł |
| 28444 | Mounted extra-wide flood lens Ø350mm, red handle | 1 604 zł |
| 28445 | Mounted frosted Fresnel lens Ø350mm, white handle | 1 907 zł |
| 28868 | Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø350mm) | 8 021 zł |
| 28812 | Carrying case for 5 lenses Ø350mm (for HMI Par 4/2.5kW & Tungsten Par 2kW); 48 x 39 x 49cm (ext. dim. L x W x H), weight (empty) 11kg | 1 454 zł |
| 28808 | Complete diffusion lens set Ø350mm w/ carrying case (28868 + 28812) | 9 464 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) | 277 zł |

27930 **Tungsten Par 5kW MO 230-240V w/o switch** 0 zł
Head fitted w/ 7m length bare ended cable (no switch), full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot

27933 **Tungsten Par 5kW MO 230-240V** 0 zł
Head fitted w/ On/Off head mounted toggle switch 60A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot
Supplied w/ gel frame Ø546mm + 4-leaf rotating barndoor Ø546mm

Additional

Tungsten halogen SE lamp type CP29 5000W 230V (G38 base, mogul bi-post) 3200K

Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K

| | | |
|-------|--|-----------|
| 28889 | Gel frame Ø546mm | 450 zł |
| 28884 | Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm) | 2 480 zł |
| 28886 | 4-leaf rotating barndoor Ø546mm | 2 015 zł |
| 28541 | Mounted spot lens Ø450mm, black handle | 2 312 zł |
| 28542 | Mounted medium flood lens Ø450mm, green handle | 2 312 zł |
| 28543 | Mounted wide flood lens Ø450mm, yellow handle | 2 312 zł |
| 28544 | Mounted extra-wide flood lens Ø450mm, red handle | 2 312 zł |
| 28545 | Mounted frosted Fresnel lens Ø450mm, white handle | 4 219 zł |
| 28888 | Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm) | 10 920 zł |
| 28813 | Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg | 2 930 zł |
| 28810 | Complete diffusion lens set Ø450mm w/ carrying case (28888 + 28813) | 13 477 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) | 277 zł |

27961 **Tungsten Par 10kW MO 230-240V** 0 zł
Head fitted w/ On/Off head mounted toggle switch 60A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot
Supplied w/ gel frame Ø546mm + 4-leaf rotating barndoor Ø546mm

Additional

Tungsten halogen SE lamp type CP29 10000W 230V (G38 base, mogul bi-post) 3200K

Tungsten halogen SE lamp type CP29 10000W 240V (G38 base, mogul bi-post) 3200K

| | | |
|-------|--|-----------|
| 28889 | Gel frame Ø546mm | 450 zł |
| 28884 | Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm) | 2 480 zł |
| 28886 | 4-leaf rotating barndoor Ø546mm | 2 015 zł |
| 28541 | Mounted spot lens Ø450mm, black handle | 2 312 zł |
| 28542 | Mounted medium flood lens Ø450mm, green handle | 2 312 zł |
| 28543 | Mounted wide flood lens Ø450mm, yellow handle | 2 312 zł |
| 28544 | Mounted extra-wide flood lens Ø450mm, red handle | 2 312 zł |
| 28545 | Mounted frosted Fresnel lens Ø450mm, white handle | 4 219 zł |
| 28888 | Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm) | 10 920 zł |
| 28813 | Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg | 2 930 zł |
| 28810 | Complete diffusion lens set Ø450mm w/ carrying case (28888 + 28813) | 13 477 zł |
| | | 0 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |

| | | |
|-------|---------------------------------------|--------|
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) | 277 zł |
|-------|---------------------------------------|--------|

Fill softlights QuartzColor Arturo

| | | | |
|---|--|--|----------|
|  | 26500 | Arturo 1 (1250W) softlight MO 230-240V Head one light-one circuit fitted w/ On/Off in-line toggle switch 8A/250V, 5m length bare ended cable, bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spiaot Supplied w/ gel frame 400 x 230mm | 3 622 zł |
|  | 26510 | Arturo 1 (1250W) softlight PO 230-240V Head one light-one circuit fitted w/ On/Off in-line toggle switch 8A/250V, 5m length bare ended cable, bottom skid, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spiaot Supplied w/ gel frame 400 x 230mm | 3 958 zł |
| Additionalis | | | |
| Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | | | |
| 28312 | Gel frame 400 x 230mm | | 293 zł |
| 28310 | Egg-crate narrow 400 x 230mm | | 1 012 zł |
| 28311 | Egg-crate standard 400 x 230mm | | 1 012 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | | 439 zł |
|  | 26520 | Arturo 2 (2500/1250W) softlight MO 230-240V Head two lights-two circuits fitted w/ On/Off <u>head mounted</u> rotary <i>select</i> switch 45A/250V, 5m length bare ended cable, bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spiaot Supplied w/ gel frame 512 x 310mm | 4 799 zł |
|  | 26530 | Arturo 2 (2500/1250W) softlight PO 230-240V Head two lights-two circuits fitted w/ On/Off <u>head mounted</u> rotary <i>select</i> switch 45A/250V, 5m length bare ended cable, bottom skid, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spiaot Supplied w/ gel frame 512 x 310mm | 6 339 zł |
| Additionalis | | | |
| Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | | | |
| Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | | | |
| 28315 | Gel frame 512 x 310mm | | 346 zł |
| 28313 | Egg-crate narrow 512 x 310mm | | 1 113 zł |
| 28314 | Egg-crate standard 512 x 310mm | | 1 113 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | | 439 zł |
| 26540 | Arturo 4 (5000/2500W) softlight MO 230-240V Head four lights-four circuits fitted w/ On/Off <u>head mounted</u> rotary <i>select</i> switch 45A/250V, 5m length bare ended cable, bottom skid, manual "U"-shape square base stirrup w/ single lock-off knob and 28mm (1½") spiaot Supplied w/ gel frame 610 x 405mm | | 7 180 zł |

| | | |
|-------------------|---|----------|
| 26550 | Arturo 4 (5000/2500W) softlight PO 230-240V Head four lights-four circuits fitted w/ On/Off head mounted rotary select switch 45A/250V, 5m length bare ended cable, bottom skid, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame 610 x 405mm | 7 926 zł |
| Additional | | |
| | Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | |
| 28318 | Gel frame 610 x 405mm | 405 zł |
| 28316 | Egg-crate narrow 610 x 405mm | 1 204 zł |
| 28317 | Egg-crate standard 610 x 405mm | 1 204 zł |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |

QuartzColor Iadi Fill

For Iadi kits, see separate price list

| | | |
|-------------------|--|--------|
| 26020 | Iadi Fill 1kW floodlight 230-240V Head fitted w/ On/Off in-line toggle switch 8A/250V, 4m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted Integrated accessories: 4-leaf barndoor + wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener | 0 zł |
| Additional | | |
| | Tungsten halogen DE linear lamp type K9 300W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type K1 500W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type K1 500W 240V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/11 (EME) 800W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/11 (EME) 800W 240V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/20 1000W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/20 1000W 240V (R7s base, MOL 119mm) 3200K | |
| 28005 | Scrim full single, frame size 176 x 135mm (W x H), w/ quick release fastener | 285 zł |
| 28004 | Scrim full double, frame size 176 x 135mm (W x H), w/ quick release fastener | 285 zł |
| 28006 | Mounted Dichroic filter (daylight), frame size 176 x 135mm (W x H), w/ quick release fastener | 796 zł |
| 28007 | Mounted diffuser filter (opal glass), frame size 176 x 135mm (W x H), w/ quick release fastener | 472 zł |
| 28003 | Set of 4 intensifying panels for Iadi barndoors | 346 zł |
| 82610 | Small clamp w/ 16mm (5/8") spigot | 112 zł |
| 82012P | Small C-clamp w/ 16mm (5/8") spigot | 162 zł |

QuartzColor Ghost

| | | |
|-------------------|---|----------|
| 27771 | Ghost 5kW suspended fill light 230-240V Main body fitted w/ 2m length bare ended cable (no switch), 28mm (1 1/8") spigot for overhead suspension and safety bond Supplied accessory on each compartment: wire mesh safety guard 3 x 3mm (239.5 x 114.5mm) | 4 664 zł |
| Additional | | |
| | Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | |
| 28100 | White diffuser cone Ø800mm x 1m length (supplied complete w/ 2 integrated support rings) | 1 257 zł |
| 28200 | Black (spot) diffuser cone Ø800mm x 1m length (supplied complete w/ 2 integrated support rings) | 0 zł |
| 28200FB | Black top/white bottom diffuser cone Ø800mm x 1m length (supplied complete w/ 2 integrated support rings) | 0 zł |

| | | |
|-------|--|--------|
| 28500 | White (soft) diffuser cone Ø800mm x 1m length (fits onto the two support rings via Velcro straps, to be ordered separately, see 28501) | 0 zł |
| 28501 | Two support rings (to be used w/ 28200, 28200FB & 28500) | 527 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |

Cyclorama softlights QuartzColor Iris

| | | |
|-------|--|----------|
| 26070 | Iris 1 (1250W) Cyclorama MO 230-240V Head one light-one circuit fitted w/ 5m length bare ended cable (no switch), manual "U"-shape flat base stirrup w/ single lock-off knob, lateral assembly plates and 28mm (1½") socket Integrated accessories: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm | 2 317 zł |
| 26080 | Iris 1 (1250W) Cyclorama PO 230-240V Head one light-one circuit fitted w/ 5m length bare ended cable (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates, 28mm (1½") socket Integrated accessories: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm Additional Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | 2 637 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |
| 26100 | Iris 2 (1250W x2) vertical Cyclorama PO 230-240V Head two lights-two circuits fitted w/ 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1½") socket Integrated accessories on each compartment: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm | 4 821 zł |
| 26110 | Iris 2 (1250W x2) horizontal Cyclorama PO 230-240V Head two lights-two circuits fitted w/ 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1½") socket Integrated accessories on each compartment: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm | 4 821 zł |
| 26090 | Iris 2 (1250W x2) vertical Cyclorama split PO 230-240V Head two lights-two circuits fitted w/ 5m length bare ended cable on each compartment (no switch), split Pole Operated "U"-shape square base stirrup (Tilt only, limited run, 1 + 1 luminaries, see specification sheet 15006 for more details) w/ lateral assembly plates, 28mm (1½") socket Integrated accessories on each compartment: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm Additional Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | 5 593 zł |
| 82013 | Hook clamp w/ 28mm (1½") socket | 439 zł |

| | | |
|----------------------------|--|----------|
| 26130 | Iris 3 (1250W x3) horizontal Cyclorama PO 230-240V Head three lights-three circuits fitted w/ 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1 1/8") socket Integrated accessories on each compartment: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm | 6 658 zł |
| | Additional | |
| | Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| 26150 | Iris 4 (1250W x4) Cyclorama PO 230-240V Head four lights-four circuits fitted w/ 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1 1/8") socket Integrated accessories on each compartment: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm | 7 724 zł |
| 26140 | Iris 4 (1250W x4) Cyclorama split PO 230-240V Head four lights-four circuits fitted w/ 5m length bare ended cable on each compartment (no switch), split Pole Operated "U"-shape square base stirrup (Tilt only, limited run, 2 + 2 luminaries, see specification sheet 15011 for more details) w/ lateral assembly plates, 28mm (1 1/8") socket Integrated accessories on each compartment: wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm | 9 189 zł |
| | Additional | |
| | Additional for IRIS | |
| | Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| 26060 | Mini Iris (1250W) Cyclorama MO 230-240V Head fitted w/ On/Off in-line toggle switch 8A/250V, 4m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted Integrated accessory: wire mesh safety guard 3 x 3mm (260 x 182mm) | 1 838 zł |
| | Additional | |
| | Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | |
| 28010 | Extended gel frame, extension 135mm, 400 x 305mm (W x H) | 490 zł |
| 3360.170 | Spare manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted (for Mini Iris Cyclorama MO) | 0 zł |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket | 439 zł |
| <h2>QuartzColor Orion</h2> | | |
| 26010 | Orion 1 (1250W) Cyclorama 230-240V Head fitted w/ 5m length bare ended cable (no switch) Supplied w/ wire mesh safety guard 3 x 3mm w/ quick release fastener (260 x 182mm) + flexible gel frame 290 x 245mm | 2 184 zł |

| Additional | | |
|---|---|-----------------|
| | Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | |
| 28001 | Flexible gel frame 290 x 245mm | 218 zł |
| Orion 4 (1250W x4) rigid Cyclorama Mk2 230-240V | | |
| 26045 | Head module 1 is fitted w/ 9-pin male power input panel connector, module 4 is fitted w/ 0.8m length cable with 9-pin female in-line connector (no switch). For luminaries arrangement. see specification sheet for more details On each compartment, supplied w/ wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener + flexible gel frame 290 x 245mm | 8 230 zł |
| Orion 4 (1250W x4) hinged Cyclorama Mk2 230-240V | | |
| 26055 | Head module 1 is fitted w/ 9-pin male power input panel connector, module 4 is fitted w/ 0.8m length cable with 9-pin female in-line connector (no switch). For luminaries arrangement. see specification sheet for more details On each compartment, supplied w/ wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener + flexible gel frame 290 x 245mm | 8 470 zł |
| Additional on next page | | |
| Additional for ORION | | |
| | Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K | |
| 28001 | Flexible gel frame 290 x 245mm | 218 zł |
| 28013 | 7m length power cable for four Orion 4 | 2 606 zł |
| 28014 | Adapter Mk1 to Mk2 for power cable 28013 | 2 469 zł |



QuartzColor Iadi Cyc


| | | |
|-------------------|--|---------------|
| 26030 | Iadi Cyc 1kW softlight 230-240V Head fitted w/ On/Off in-line toggle switch 8A/250V, 4m length bare ended cable and manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted Integrated accessories: 4-leaf barndoor + wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener | 0 zł |
| Additional | | |
| | Tungsten halogen DE linear lamp type K9 300W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type K1 500W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type K1 500W 240V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/11 (EME) 800W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/11 (EME) 800W 240V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/20 1000W 230V (R7s base, MOL 119mm) 3200K | |
| | Tungsten halogen DE linear lamp type P2/20 1000W 240V (R7s base, MOL 119mm) 3200K | |
| 28005 | Scrim full single, frame size 176 x 135mm (W x H), w/ quick release fastener | 285 zł |
| 28004 | Scrim full double, frame size 176 x 135mm (W x H), w/ quick release fastener | 285 zł |
| 28006 | Mounted Dichroic filter (daylight), frame size 176 x 135mm (W x H), w/ quick release fastener | 796 zł |
| 28007 | Mounted diffuser filter (opal glass), frame size 176 x 135mm (W x H), w/ quick release fastener | 472 zł |
| 28003 | Set of 4 intensifying panels for Iadi barndoors | 346 zł |
| 82610 | Small clamp w/ 16mm (5/8") spigot | 112 zł |
| 82012P | Small C-clamp w/ 16mm (5/8") spigot | 162 zł |

Daylight standard spotlights

QuartzColor HMI Fresnels

For HMI Fresnel **PO** versions, please contact us

| | | |
|---|---|-------------|
|  | <p>27020 HMI Fresnel 200W 220-240V Head fitted w/ Fresnel lens Ø90mm, 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket Supplied w/ 7m length head to ballast extension cable fitted w/ male and female 7-pin Amphenol® twist lock connectors + gel frame Ø110mm + 4-leaf rotating barndoor Ø110mm</p> | <p>0 zł</p> |
| <p>27021</p> | <p>HMI Fresnel 200W 220-240V + ballast - SET Head fitted w/ Fresnel lens Ø90mm, 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket Supplied w/ <u>electronic ballast 200W</u> (7-pin Amphenol® female connector) + 7m length head to ballast extension cable fitted w/ male and female 7-pin Amphenol® twist lock connectors + gel frame Ø110mm + <u>scrim set 4 pieces</u> (full single + full double + half single + half double; Ø110mm) + 4-leaf rotating barndoor Ø110mm + plywood <u>flight case</u></p> | <p>0 zł</p> |
| <p>Additional on next page Additional</p> | | |
| <p>42201</p> | <p>HMI/MSR (Osram/Philips®) SE HR 200W lamp (GZY9.5 base) 6000K</p> | |
| <p>25921</p> | <p>Electronic ballast 200W (110/220V, 50/60Hz, 7-pin Amphenol® female connector) w/ auto voltage selection</p> | |
| <p>HMI Fresnel 200W can be used w/ other brand 200W ballast without additional adapter cable</p> | | |
| <p>28823</p> | <p>7m head to ballast extension cable (for HMI Fresnel & Par 200W) fitted w/ male and female</p> | |
| <p>28080</p> | <p>7-pin Amphenol® twist lock connectors (not for 120V products) Gel frame Ø110mm (not for 120V products)</p> | |
| <p>28301</p> | <p>Scrim set 4 pieces (full single + full double + half single + half double; Ø110mm)</p> | |
| <p>28104</p> | <p>Cone w/ variable aperture Ø110mm</p> | |
| <p>28040</p> | <p>4-leaf rotating barndoor Ø110mm (not for 120V products)</p> | |
| <p>28108</p> | <p>8-leaf rotating barndoor Ø110mm</p> | |
| <p>5320/170</p> | <p>Spare manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket (for HMI Fresnel 200W)</p> | |
| <p>82013</p> | <p>Hook clamp w/ 28mm (1 1/8") socket</p> | |
| <p>28152</p> | <p>Accessory safety bond (Ø2mm, length 40cm)</p> | |
| <td data-bbox="424 1149 1238 1285"> <p>27030 HMI Fresnel 400W 220-240V Head fitted w/ Fresnel lens Ø130mm, 0.8m length cable w/ 7-pin in-line Schaultbau® male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket Supplied w/ 7m length head to ballast extension cable fitted w/ male and female 7-pin Schaultbau® connectors + gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm</p> </td> <td data-bbox="1238 1149 1442 1285"> <p>0 zł</p> </td> | <p>27030 HMI Fresnel 400W 220-240V Head fitted w/ Fresnel lens Ø130mm, 0.8m length cable w/ 7-pin in-line Schaultbau® male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket Supplied w/ 7m length head to ballast extension cable fitted w/ male and female 7-pin Schaultbau® connectors + gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm</p> | <p>0 zł</p> |
|  | <p>27031 HMI Fresnel 400W 220-240V + ballast - SET Head fitted w/ Fresnel lens Ø130mm, 0.8m length cable w/ 7-pin in-line Schaultbau® male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket Supplied w/ <u>electronic ballast 400/575W</u> (7-pin Schaultbau® female connector) + 7m length head to ballast extension cable fitted w/ male and female 7-pin Schaultbau® connectors + gel frame Ø168mm + <u>scrim set 4 pieces</u> (full single + full double + half single + half double; Ø168mm) + 4-leaf rotating barndoor Ø168mm + plywood <u>flight case</u></p> | <p>0 zł</p> |
| <p>Additional</p> | | |
| <p>42200</p> | <p>HMI/MSR (Osram/Philips®) SE HR 400W lamp (GZY9.5 base) 6000K</p> | |
| <p>25932</p> | <p>Electronic ballast 575/400W (110/220V, 50/60Hz, 7-pin Schaultbau® & 7-pin Amphenol® female connectors) w/ auto voltage selection (needs adaptor for use w/ 575W QC head)</p> | |
| <p>HMI Fresnel 400W can be used w/ other brand 400W ballast without additional adapter cable</p> | | |
| <p>28833</p> | <p>7m head to ballast extension cable (for HMI Fresnel 400W) fitted w/ male and female 7-pin</p> | |
| <p>28047</p> | <p>Schaultbau® connectors (not for 120V products) Gel frame Ø168mm</p> | |
| <p>28309</p> | <p>Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm)</p> | |
| <p>28049</p> | <p>Cone w/ variable aperture Ø168mm</p> | |
| <p>28048</p> | <p>4-leaf rotating barndoor Ø168mm</p> | |
| <p>28837</p> | <p>8-leaf rotating barndoor Ø168mm</p> | |
| <p>5340/170</p> | <p>Spare manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket (for HMI Fresnel 400W)</p> | |

| | | |
|---|---|--|
| 82013 | Hook clamp w/ 28mm (1½") socket | |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) | |
| | | |
|  | 27040 | HMI Fresnel 575W 220-240V 0 zł |
| | | Head fitted w/ Fresnel lens Ø130mm, 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spigot |
| | | Supplied w/ 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm |
| Additional | | |
| 42101 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K | |
| 25941 | Electronic ballast 575W (110/220V, 50/60Hz, 7-pin Veam® type female connector) w/ auto voltage selection | |
| 25030 | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection | |
| 25030DMX | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control | |
| 25220 | Magnetic ballast BCS-575W/E (220-240V, 50Hz, 7-pin Veam® type female connector) | |
| <i>Magnetic ballast w/ DMX control on request only</i> | | |
| 28843 | Adapter cable for use w/ other brand 575W ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 575W) | |
| 28201 | 8m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) | |
| 28202 | 15m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) | |
| 28849 | Gel frame Ø198mm | |
| 28844 | Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm) | |
| 28840 | Cone w/ variable aperture Ø200mm | |
| 28846 | 4-leaf rotating barndoor Ø200mm | |
| 28847 | 8-leaf rotating barndoor Ø200mm | |
| 82013 | Hook clamp w/ 28mm (1½") socket | |
| 28151 | Accessory safety bond (Ø2mm, length 50cm) | |
| | | |
| 27050 | HMI Fresnel 1.2kW 220-240V 0 zł | |
| | | Head fitted w/ Fresnel lens Ø175mm, 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1½") spigot |
| | | Supplied w/ 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm |
| Additional | | |
| 42102 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K | |
| 25030 | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection | |
| 25030DMX | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control | |
| 25230 | Magnetic ballast BCS-1.2kW/E (220-240V, 50Hz, 7-pin Veam® type female connector) | |
| <i>Magnetic ballast w/ DMX control on request only</i> | | |
| 28853 | Adapter cable for use w/ other brand 1.2kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 1.2kW) | |
| 28203 | 8m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) | |
| 28204 | 15m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) | |
| 28859 | Gel frame Ø258mm | |
| 28304 | Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm) | |
| 28850 | Cone w/ variable aperture Ø269mm | |
| 28050 | 4-leaf rotating barndoor Ø269mm | |
| 28857 | 8-leaf rotating barndoor Ø269mm | |
| 5360.170 | Spare manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1½") spigot (for HMI Fresnel 1.2kW) | |
| 82013 | Hook clamp w/ 28mm (1½") socket | |
| 28151 | Accessory safety bond (Ø2mm, length 50cm) | |
| | | |

| | |
|--|--|
| 27060 | HMI Fresnel 2.5kW 220-240V Head fitted w/ Fresnel lens Ø250mm, 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm |
| Additional | |
| 42103 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 2500W lamp (G38 base) 6000K |
| 25040 | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection |
| 25040DMX | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control |
| 25050 | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) |
| 25050DMX | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control |
| 25240 | Magnetic ballast BCS-2.5kW/E (220-240V, 50Hz, 7-pin Veam® type female connector) |
| <i>Magnetic ballast w/ DMX control on request only</i> | |
| 28863 | Adapter cable for use w/ other brand 2.5kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 2.5kW & Par 4/2.5kW) |
| 28205 | 8m head to ballast extension cable (for HMI Fresnel 2.5kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28206 | 15m head to ballast extension cable (for HMI Fresnel 2.5kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28093 | Gel frame Ø323mm |
| 28306 | Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm) |
| 28090 | Cone small aperture Ø323mm |
| 28091 | Cone medium aperture Ø323mm |
| 28092 | Cone large aperture Ø323mm |
| 28114 | 4-leaf rotating barndoor Ø323mm |
| 28071 | 8-leaf rotating barndoor Ø323mm |
| 5370.170 | Spare manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot (for HMI Fresnel 2.5kW) |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 28150 | Accessory safety bond (Ø2mm, length 70cm) |
| HMI Fresnel 4kW 220-240V | |
| 27070 | Head fitted w/ Fresnel lens Ø300mm, 0.8m length cable w/ 9-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ 8m length head to ballast extension cable fitted w/ 9-pin male and female bayonet Veam® type connectors + adaptor cable 4kW/2.5kW + gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm |
| Additional | |
| 42104 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 4000W lamp (G38 base) 6000K |
| 25050 | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) |
| 25050DMX | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control |
| 25060 | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) |
| 25060DMX | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control |
| 25250 | Magnetic ballast BCS-4kW/E (220-240V, 50Hz, 9-pin Veam® type female connector) |
| <i>Magnetic ballast w/ DMX control on request only</i> | |
| 28873 | Adapter cable for use w/ other brand 4kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 4kW & Par 4/2.5kW) |
| 28207 | 8m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28208 | 15m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28097 | Gel frame Ø408mm |
| 28307 | Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm) |
| 28094 | Cone small aperture Ø401mm |
| 28095 | Cone small medium Ø401mm |
| 28096 | Cone large aperture Ø401mm |
| 28115 | 4-leaf rotating barndoor Ø401mm |
| 28075 | 8-leaf rotating barndoor Ø401mm |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) |

| | |
|-------------------|--|
| 27081 | HMI Fresnel 6kW Compact 220-240V Head fitted w/ Proprietary Fresnel lens Ø450mm, 0.8m length cable w/ 16-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") socket Supplied w/ 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + gel frame Ø546mm + 4-leaf rotating barndoor Ø546mm |
| Additional | |
| 42206 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 6000W lamp (GY38 base) 6000K |
| 25060 | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) |
| 25060DMX | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control |
| 25070 | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) |
| 25070DMX | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control |
| 25260 | Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) |
| 25260DMX | Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) w/ DMX control |
| 28883 | Adapter cable for use w/ other brand 6kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 6kW Compact) |
| 28209 | 8m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28210 | 1.5m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (for both 230V & 120V use) |
| 28889 | Gel frame Ø546mm |
| 28884 | Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm) |
| 28886 | 4-leaf rotating barndoor Ø546mm |
| 28887 | 8-leaf rotating barndoor Ø546mm |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) |

QuartzColor HMI Pars

For HMI Par **PO** versions, please contact us

| | |
|-------------------|---|
| 27520 | HMI Par 200W 220-240V Head fitted w/ 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 16mm (5/8") socket Supplied w/ 7m length head to ballast extension cable fitted w/ 7-pin male and female Amphenol® twist lock connectors + gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm + diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø146mm; & frosted Fresnel Ø150mm) + lens carrying case |
| 27521 | HMI Par 200W 220-240V + ballast - SET Head fitted w/ 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 16mm (5/8") socket Supplied w/ electronic ballast 200W (7-pin Amphenol® female connector) + 7m length head to ballast extension cable fitted w/ 7-pin male and female Amphenol® twist lock connectors + gel frame Ø168mm + scrim set 4 pieces (full single + full double + half single + half double; Ø168mm) + diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø146mm; & frosted Fresnel Ø150mm) + 4-leaf rotating barndoor Ø168mm + plywood flight case |
| Additional | |
| 42201 | HMI/MSR (Osram/Philips®) SE HR 200W lamp (GZY9.5 base) 6000K |
| 25921 | Electronic ballast 200W (110/220V, 50/60Hz, 7-pin Amphenol® female connector) w/ auto voltage selection <i>HMI Par 200W can be used w/ other brand 200W ballast without additional adapter cable</i> |
| 28823 | 7m head to ballast extension cable (for HMI Fresnel & Par 200W) fitted w/ 7-pin male and female Amphenol® twist lock connectors (not for 120V products) |
| 28047 | Gel frame Ø168mm |
| 28309 | Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm) |
| 28048 | 4-leaf rotating barndoor Ø168mm |
| 28837 | 8-leaf rotating barndoor Ø168mm |
| 28838NS | Mounted spot proprietary lens Ø146mm, black handle |
| 28838MF | Mounted medium flood proprietary lens Ø146mm, green handle |
| 28838WF | Mounted wide flood proprietary lens Ø1465mm, yellow handle |
| 28838EW | Mounted extra-wide flood proprietary lens Ø146mm, red handle |
| 28838FF | Mounted frosted Fresnel proprietary lens Ø150mm, white handle |
| 28828 | Diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø146mm; & frosted Fresnel Ø150mm) |

| | |
|--|--|
| 28811 | Carrying case for 5 lenses up to Ø205mm (for HMI Par 200 & 575W, OneLight™ HMI Par 200 & 575W); 28 x 34 x 28cm (ext. dim. L x W x H) weight (empty) 4.5kg |
| 28804 | Complete diffusion proprietary lens set w/ carrying case (28828 + 28811) |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) |
| | |
| 27540 | <p>HMI Par 575W 220-240V</p> <p>Head fitted w/ 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 28mm (1 1/8") spigot</p> <p>Supplied w/ 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø229mm + 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) + lens carrying case</p> |
| | |
| 27541 | <p>HMI Par 575W 220-240V + ballast - SET</p> <p>Head fitted w/ 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 28mm (1 1/8") spigot</p> <p>Supplied w/ <u>electronic ballast 575W</u> (7-pin Veam® type female connector) + 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø229mm + <u>scrim set 4 pieces</u> (full single + full double + half single + half double; Ø229mm) + 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) + lens carrying case</p> |
| | |
| Additional | |
| 42101 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K |
| 25941 | Electronic ballast 575W (110/220V, 50/60Hz, 7-pin Veam® type female connector) w/ auto voltage selection |
| 25030 | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection |
| 25030DMX | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control |
| 25220 | Magnetic ballast BCS-575W/E (220-240V, 50Hz, 7-pin Veam® type female connector) |
| <i>Magnetic ballast w/ DMX control on request only</i> | |
| 28843 | Adapter cable for use w/ other brand 575W ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 575W) |
| 28201 | 8m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28202 | 15m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28086 | Gel frame Ø229mm |
| 28305 | Scrim set 4 pieces (full single + full double + half single + half double; Ø229mm) |
| 28110 | 4-leaf rotating barndoor Ø230mm |
| 28111 | 8-leaf rotating barndoor Ø230mm |
| 28838NS | Mounted spot lens Ø205mm, black handle |
| 28838MF | Mounted medium flood lens Ø205mm, green handle |
| 28838WF | Mounted wide flood lens Ø205mm, yellow handle |
| 28838EW | Mounted extra-wide flood lens Ø205mm, red handle |
| 28838FF | Mounted frosted Fresnel lens Ø200mm, white handle |
| 28838 | Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) |
| 28811 | Carrying case for 5 lenses up to Ø205mm (for HMI Par 200 & 575W, OneLight™ HMI Par 200 & 575W); 28 x 34 x 28cm (ext. dim. L x W x H) weight (empty) 4.5kg |
| 28805 | Complete diffusion lens set Ø200/205mm w/ carrying case (28838 + 28811) |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) |
| | |
| 27550 | <p>HMI Par 1.2kW 220V</p> <p>Head fitted w/ 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot</p> <p>Supplied w/ 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø323mm + diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel: Ø250mm) + lens carrying case</p> |

Additional

| | |
|--|--|
| 42102 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K |
| 25030 | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection |
| 25030DMX | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control |
| 25040 | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection |
| 25040DMX | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control |
| 25230 | Magnetic ballast BCS-1.2kW/E (220-240V, 50Hz, 7-pin Veam® type female connector) |
| <i>Magnetic ballast w/ DMX control on request only</i> | |
| 28853 | Adapter cable for use w/ other brand 1.2kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 1.2kW) |
| 28203 | 8m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28204 | 15m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28093 | Gel frame Ø323mm |
| 28306 | Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm) |
| 28114 | 4-leaf rotating barndoor Ø323mm |
| 28071 | 8-leaf rotating barndoor Ø323mm |
| 28341 | Mounted spot proprietary lens Ø250mm, black handle |
| 28342 | Mounted medium flood proprietary lens Ø250mm, green handle |
| 28343 | Mounted wide flood proprietary lens Ø250mm, yellow handle |
| 28344 | Mounted extra-wide flood proprietary lens Ø250mm, red handle |
| 28345 | Mounted frosted Fresnel proprietary lens Ø250mm, white handle |
| 28848 | Diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm) |
| 28814 | Carrying case for 5 lenses Ø250mm (for HMI Par 1.2kW, OneLight™ HMI Par 1.2kW & Tungsten Par 1kW); 38 x 43 x 42cm (ext. dim. L x W x H) weight (empty) 7kg |
| 28806 | Complete diffusion proprietary lens set Ø250mm w/ carrying case (28848 + 28814) |
| 82013 | Hook clamp w/ 28mm (1½") socket |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) |

27570

HMI Par 4/2.5kW 220-240V

Head fitted w/ 0.8m length cable w/ 9-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot

Supplied w/ 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø401mm + diffusion **proprietary** lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø350mm) + lens carrying case + adapter cable for use w/ 2.5kW ballast

Additional

| | |
|---|---|
| 42103 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 2500W lamp (G38 base) 6000K |
| 42104 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 4000W lamp (G38 base) 6000K |
| 25040 | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection |
| 25040DMX | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control |
| 25050 | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) |
| 25050DMX | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control |
| 25240 | Magnetic ballast BCS-2.5kW/E (220-240V, 50Hz, 7-pin Veam® type female connector) |
| 25250 | Magnetic ballast BCS-4kW/E (220-240V, 50Hz, 9-pin Veam® type female connector) |
| <i>Magnetic ballasts w/ DMX control on request only</i> | |
| 28032 | Adaptor cable for 2.5kW use, fitted w/ 9-pin male and female bayonet Veam® type connectors (for HMI Par 4/2.5kW) |
| 28863 | Adapter cable for use w/ other brand 2.5kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 2.5kW & Par 4/2.5kW) |
| 28873 | Adapter cable for use w/ other brand 4kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 4kW & Par 4/2.5kW) |
| 28207 | 8m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28208 | 15m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28097 | Gel frame Ø408mm |
| 28307 | Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm) |
| 28115 | 4-leaf rotating barndoor Ø401mm |
| 28075 | 8-leaf rotating barndoor Ø401mm |
| 28441 | Mounted spot proprietary lens Ø350mm, black handle |
| 28442 | Mounted medium flood proprietary lens Ø350mm, green handle |

| | |
|-------------------|--|
| 28443 | Mounted wide flood proprietary lens Ø350mm, yellow handle |
| 28444 | Mounted extra-wide flood proprietary lens Ø350mm, red handle |
| 28445 | Mounted frosted Fresnel proprietary lens Ø350mm, white handle |
| 28868 | Diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø350mm) |
| 28812 | Carrying case for 5 lenses Ø350mm (for HMI Par 4/2.5kW & Tungsten Par 2kW); 48 x 39 x 49cm (ext. dim. L x W x H), weight (empty) 11kg |
| 28808 | Complete diffusion proprietary lens set Ø350mm w/ carrying case (28868 + 28812) |
| 82013 | Hook clamp w/ 28mm (1½") socket |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) |
| | |
| 27588 | HMI Par 6kW Compact 220-240V Head fitted w/ 0.8m length cable w/ 16-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot Supplied w/ 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø546mm + diffusion proprietary lens set 5 pieces (full single + full double + half single + half double + frosted Fresnel; Ø450mm) + lens carrying case |
| Additional | |
| 42206 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 6000W lamp (GY38 base) 6000K |
| 25060 | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) |
| 25060DMX | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control |
| 25070 | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) |
| 25070DMX | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control |
| 25260 | Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) |
| 25260DMX | Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) w/ DMX control |
| 28883 | Adapter cable for use w/ other brand 6kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 6kW Compact) |
| 28209 | 8m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28210 | 15m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (for both 230V & 120V use) |
| 28889 | Gel frame Ø546mm |
| 28884 | Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm) |
| 28886 | 4-leaf rotating barndoor Ø546mm |
| 28887 | 8-leaf rotating barndoor Ø546mm |
| 28541 | Mounted spot proprietary lens Ø450mm, black handle |
| 28542 | Mounted medium flood proprietary lens Ø450mm, green handle |
| 28543 | Mounted wide flood proprietary lens Ø450mm, yellow handle |
| 28544 | Mounted extra-wide flood proprietary lens Ø450mm, red handle |
| 28545 | Mounted frosted Fresnel proprietary lens Ø450mm, white handle |
| 28888 | Diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm) |
| 28813 | Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg |
| 28810 | Complete diffusion proprietary lens set Ø450mm w/ carrying case (28888 + 28813) |
| 82013 | Hook clamp w/ 28mm (1½") socket |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) |
| | |
| 27590 | HMI Par 12/6kW 220-240V Head fitted w/ 0.8m length cable w/ 8-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot Supplied w/ 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø546mm + Diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm) + lens carrying case |
| Additional | |
| 42206 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 6000W lamp (GY38 base) 6000K |
| 42212 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 12000W lamp (GY38 base) 6000K |
| 25060 | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) |
| 25060DMX | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control |
| 25070 | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) |
| 25070DMX | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control |

| | |
|--|---|
| 25260 | Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) |
| 25260DMX | Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) w/ DMX control |
| 25270 | Magnetic ballast BCS-12kW/E (220-240V, 50Hz, 8-pin Veam® type female connector) |
| <i>Magnetic ballast w/ DMX control on request only</i> | |
| 28894 | Adaptor cable for 6kW use, fitted w/ 8-pin male and female bayonet Veam® type connectors |
| 28896 | Adapter cable for use w/ other brand 12/6kW ballast (to be specified when ordering) 25cm length (for HMI Par 12/6kW) |
| 28211 | 8m head to ballast extension cable (for HMI Par 12/6kW) fitted w/ 8-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28212 | 15m head to ballast extension cable (for HMI Par 12/6kW) fitted w/ 8-pin male and female bayonet Veam® type connectors (not for 120V products) |
| 28889 | Gel frame Ø546mm |
| 28884 | Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm) |
| 28886 | 4-leaf rotating barndoor Ø546mm |
| 28887 | 8-leaf rotating barndoor Ø546mm |
| 28541 | Mounted spot proprietary lens Ø450mm, black handle |
| 28542 | Mounted medium flood proprietary lens Ø450mm, green handle |
| 28543 | Mounted wide flood proprietary lens Ø450mm, yellow handle |
| 28544 | Mounted extra-wide flood proprietary lens Ø450mm, red handle |
| 28545 | Mounted frosted Fresnel proprietary lens Ø450mm, white handle |
| 28888 | Diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm) |
| 28813 | Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg |
| 28810 | Complete diffusion lens set Ø450mm w/ carrying case (28888 + 28813) |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 82002 | Safety cable 50kg (Ø4mm, length 70cm) |

Daylight compact spotlights

QuartzColor OneLight™ HMI Fresnels

| | |
|----------|---|
| 27044 | <p>OneLight™ HMI Fresnel 575W 90-260V</p> <p>Unit supplied w/ integrated High Frequency electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø130mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot</p> <p>Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K</p> |
| 27044DMX | <p>OneLight™ HMI Fresnel 575W 90-260V DMX</p> <p>Unit supplied w/ integrated High Frequency electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø130mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, DMX card, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot</p> <p>Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K</p> <p>Additional</p> |
| 42108 | MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base, medium bi-post) 6000K |
| 27044EB | <i>Spare</i> High Frequency electronic ballast 575W (90-260V, 50/60Hz, for OneLight™ 575W Fresnel) |
| 28900 | DMX card for OneLight™ Fresnels & Pars |
| 28849 | Gel frame Ø198mm |
| 28844 | Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm) |
| 28840 | Cone w/ variable aperture Ø200mm |
| 28846 | 4-leaf rotating barndoor Ø200mm |
| 28847 | 8-leaf rotating barndoor Ø200mm |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 28151 | Accessory safety bond (Ø2mm, length 50cm) |
| 27054 | <p>OneLight™ HMI Fresnel 1.2kW 90-260V</p> |

Unit supplied w/ integrated High Frequency electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø175mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") spigot

Supplied w/ gel frame Ø258mm and 4-leaf rotating barndoor Ø269mm + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

27054DMX

OneLight™ HMI Fresnel 1.2kW 90-260v DMX

Unit supplied w/ integrated High Frequency electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø175mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, DMX card, full bottom skid, manual "U"-shape flat base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") spigot

Supplied w/ gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

Additional

42203

MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K

27054EB

Spare High Frequency electronic ballast 1.2kW (90-260V, 50/60Hz, for OneLight™ 1.2kW Fresnel)

28900

DMX card for OneLight™ Fresnels & Pars

28859

Gel frame Ø258mm

28304

Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm)

28850

Cone w/ variable aperture Ø269mm

28050

4-leaf rotating barndoor Ø269mm

28857

8-leaf rotating barndoor Ø269mm

82013

Hook clamp w/ 28mm (1 1/8") socket

28151

Accessory safety bond (Ø2mm, length 50cm)

QuartzColor OneLight™ HMI Pars

27544E

OneLight™ HMI Par 575W 90-260v w/o lens system

Unit supplied w/ integrated High Frequency electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot

Supplied w/ 4-leaf rotating barndoor Ø230mm + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K

27544

OneLight™ HMI Par 575W 90-260v

Unit supplied w/ integrated High Frequency electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot

Supplied w/ 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) + lens carrying case + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K

27544DMX

OneLight™ HMI Par 575W 90-260v DMX

Unit supplied w/ integrated High Frequency electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, DMX card, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot

Supplied w/ 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) + lens carrying case MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K

Additional

42108

MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base, medium bi-post) 6000K

27544EB

Spare High Frequency electronic ballast 575W (90-260V, 50/60Hz, for OneLight™ 575W Par)

28900

DMX card for OneLight™ Fresnels & Pars

28086

Gel frame Ø229mm

28305

Scrim set 4 pieces (full single + full double + half single + half double; Ø229mm)

28110

4-leaf rotating barndoor Ø230mm

28111

8-leaf rotating barndoor Ø230mm

28838NS

Mounted spot lens Ø205mm, black handle

28838MF

Mounted medium flood lens Ø205mm, green handle

28838WF

Mounted wide flood lens Ø205mm, yellow handle

28838EW

Mounted extra-wide flood lens Ø205mm, red handle

| | |
|----------|--|
| 28838FF | Mounted frosted Fresnel lens Ø200mm, white handle |
| 28838 | Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) |
| 28811 | Carrying case for 5 lenses up to Ø205mm (for HMI Par 200 & 575W, OneLight™ HMI Par 200 & 575W); 28 x 34 x 28cm (ext dim L x W x H) weight (empty) 4.5kg |
| 28805 | Complete diffusion lens set Ø200/205mm w/ carrying case (28838 + 28811) |
| 28838NSS | Mounted spot lens Ø205mm, black handle, w/ anti light-spill ring |
| 28838MFS | Mounted medium flood lens Ø205mm, green handle, w/ anti light-spill ring |
| 28838WFS | Mounted wide flood lens Ø205mm, yellow handle, w/ anti light-spill ring |
| 28838EWS | Mounted extra-wide flood lens Ø205mm, red handle, w/ anti light-spill ring |
| 28838FFS | Mounted frosted Fresnel lens Ø200mm, white handle, w/ anti light-spill ring |
| 28838SPR | Diffusion lens set 5 pieces w/ anti light-spill ring (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) |
| 28805SPR | Complete diffusion lens set Ø200/205mm w/ anti light-spill ring and carrying case (28838SPR + 28811) |
| 82013 | Hook clamp w/ 28mm (1 1/8") socket |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) |

27554E

OneLight™ HMI Par 1.2kW 90-260V w/o lens system

Unit supplied w/ integrated High Frequency electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape square base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") socket

Supplied w/ 4-leaf rotating barndoor Ø323mm + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

27554

OneLight™ HMI Par 1.2kW 90-260V

Unit supplied w/ integrated High Frequency electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape square base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") socket

Supplied w/ 4-leaf rotating barndoor Ø323mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm) + lens carrying case + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

27554DMX

OneLight™ HMI Par 1.2kW 90-260V DMX

Unit supplied w/ integrated High Frequency electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, DMX card, full bottom skid, manual "U"-shape square base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") socket

Supplied w/ 4-leaf rotating barndoor Ø323mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm) + lens carrying case + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

Additional

42203

MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K

27554EB

Spare High Frequency electronic ballast 1.2kW (90-260V, 50/60Hz, for OneLight™ 1.2kW Par)

28900

DMX card for OneLight™ Fresnels & Pars

28093

Gel frame Ø323mm

28306

Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)

28114

4-leaf rotating barndoor Ø323mm

28071

8-leaf rotating barndoor Ø323mm

28341

Mounted spot lens Ø250mm, black handle

28342

Mounted medium flood lens Ø250mm, green handle

28343

Mounted wide flood lens Ø250mm, yellow handle

28344

Mounted extra-wide flood lens Ø250mm, red handle

28345

Mounted frosted Fresnel lens Ø250mm, white handle

28848

Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm)

28814

Carrying case for 5 lenses Ø250mm (for HMI Par 1.2kW, OneLight™ HMI Par 1.2kW & Tungsten Par 1kW);
38 x 43 x 42cm (ext dim L x W x H) weight (empty) 7kg

28806

Complete diffusion lens set Ø250mm w/ carrying case (28848 + 28814)

Diffusion lens w/ anti light-spill ring on request

82013

Hook clamp w/ 28mm (1 1/8") socket

82002

Safety cable 50kg (Ø4mm, length 70cm)

QuartzColor Ceramic Fresnels

27018

Ceramic Fresnel DM 150W 220-240V 4200K+3000K

Unit supplied w/ integrated electronic ballast 150W & 220~240V/50Hz power supply, On/Off in-line toggle switch 8A/250V, 4.5m length bare ended cable, Fresnel lens Ø130mm, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") socket
Supplied w/ gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm + Philips® Mastercolor CDM 150W SA/T 150/942 4200K and CDM 150W SA/T 150/830 3000K lamps

| Additional | |
|-------------------|---|
| 42926 | Mastercolor CDM (Philips®) SE 150W SA/T 150/942 lamp (G12 base) 4200K |
| 42207 | Mastercolor CDM (Philips®) SE 150W SA/T 150/830 lamp (G12 base) 3000K |
| 5315/1 | <i>Spare</i> High Frequency electronic ballast 150W (220-240V, 50Hz, for Ceramic Fresnel DM 150W) |
| 28047 | Gel frame Ø168mm |
| 28309 | Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm) |
| 28049 | Cone w/ variable aperture Ø168mm |
| 28048 | 4-leaf rotating barndoor Ø168mm |
| 28837 | 8-leaf rotating barndoor Ø168mm |
| 82013 | Hook clamp w/ 28mm (1½") socket |
| 28152 | Accessory safety bond (Ø2mm, length 40cm) |

27028 **Ceramic Fresnel 250W 90-265V 6000K+3200K**
Unit supplied w/ integrated electronic ballast 250W & universal voltage (90-265V, 50/60Hz), local On/Off power switch, 5m length bare ended cable, Fresnel lens Ø130mm, full bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") socket
Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm + Philips® Ceramic MSR 250W SE HR 6000K and Ceramic ST 250W SE HR 3200K lamps

| Additional | |
|-------------------|---|
| 42250 | Ceramic MSR (Philips®) SE HR 250W lamp (GZY9.5 base) 6000K |
| 5325/1 | Ceramic ST (Philips®) SE HR 250W lamp (GZY9.5 base) 3200K |
| 5325/25 | <i>Spare</i> High Frequency electronic ballast 250W (90-265V, 50/60Hz, ballast + igniter, for Ceramic Fresnel 250W) |
| 28849 | Gel frame Ø198mm |
| 28844 | Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm) |
| 28840 | Cone w/ variable aperture Ø200mm |
| 28846 | 4-leaf rotating barndoor Ø200mm |
| 28847 | 8-leaf rotating barndoor Ø200mm |
| 82013 | Hook clamp w/ 28mm (1½") socket |
| 28151 | Accessory safety bond (Ø2mm, length 50cm) |

Miscellaneous

QuartzColor ballasts for HMI

| Electronic ballasts 110/220V or more, see below | |
|--|---|
| 25921 | Electronic ballast 200W (110/220V, 50/60Hz, 7-pin Amphenol® female connector) w/ auto voltage selection |
| 25932 | Electronic ballast 575/400W (110/220V, 50/60Hz, 7-pin Schaltbau® & 7-pin Amphenol® female connectors) w/ auto voltage selection |
| 25941 | Electronic ballast 575W (110/220V, 50/60Hz, 7-pin Veam® type female connector) w/ auto voltage selection |
| 25030 | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection |
| 25030DMX | Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control |
| 25040 | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection |
| 25040DMX | Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control |
| 25440 | Electronic ballast 2.5/1.2kW (190-250V, 50/60Hz, 7-pin Veam® type female connectors) w/ dual socket autoselecting |
| 25440DMX | Electronic ballast 2.5/1.2kW (190-250V, 50/60Hz, 7-pin Veam® type female connectors) w/ dual socket autoselecting and DMX control |
| 25050 | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) |
| 25050DMX | Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control |
| 25060 | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) |
| 25060DMX | Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control |

| | |
|----------|---|
| 25070 | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) |
| 25070DMX | Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control |

For the Power Factor of each model, please refer in corresponding data sheet

Magnetic ballasts 220-240V except 6kW, see below

| | |
|----------|---|
| 25220 | Magnetic ballast BCS-575W/E (220-240V, 50Hz, 7-pin Veam® type female connector) |
| 25230 | Magnetic ballast BCS-1.2kW/E (220-240V, 50Hz, 7-pin Veam® type female connector) |
| 25240 | Magnetic ballast BCS-2.5kW/E (220-240V, 50Hz, 7-pin Veam® type female connector) |
| 25250 | Magnetic ballast BCS-4kW/E (220-240V, 50Hz, 9-pin Veam® type female connector) |
| 25260 | Magnetic ballast BCS-6kW/E (208 -240V, 50/ 60 Hz, 16-pin Veam® type female connector) |
| 25260DMX | Magnetic ballast BCS-6kW/E (208 -240V, 50/ 60 Hz, 16-pin Veam® type female connector) w/ DMX control |
| 25270 | Magnetic ballast BCS-12kW/E (220-240V, 50Hz, 8-pin Veam® type female connector) |

Other magnetic ballast w/ DMX control on request only

Lamps

Incandescent lamps, screw type

Incandescent (Argaphoto) lamp type P2/1 500W 230V (E27 base)
 Incandescent (Argaphoto) lamp type P2/1 500W 240V (E27 base)

Tungsten halogen SE (single ended) lamps, 2-pin

Tungsten halogen SE lamp type CP81 (FMF) 300W 230V (GY9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type CP81 (FSK) 300W 240V (GY9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type CP82 (FRH) **500W** 230V (GY9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type CP82 (FRJ) 500W 240V (GY9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type A1/233 (DYR) **650W** 230V (GZ9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type A1/233 (DYR) 650W 240V (GZ9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type CP89 (FRL) 650W 230V (GY9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type CP89 (FRM) 650W 240V (GY9.5 base, oriented 2-pin) 3200K
 Tungsten halogen SE lamp type CP40 (FKJ) **1000W** 230V (G22 base, medium bi-post) 3200K
 Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K
 Tungsten halogen SE lamp type CP41 (FKK) **2000W** 230V (G38 base, mogul bi-post) 3200K
 Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K
 Tungsten halogen SE lamp type CP29 **5000W** 230V (G38 base, mogul bi-post) 3200K
 Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K
 Tungsten halogen SE lamp type CP83 **10000W** 230V (G38 base, mogul bi-post) 3200K
 Tungsten halogen SE lamp type CP83 10000W 240V (G38 base, mogul bi-post) 3200K

Tungsten halogen SE (single ended) lamps twin filament, 4-pin

| |
|--|
| Tungsten halogen SE twin filament lamp type CP30 1250/1250W 230V (GX38q base) 3200K |
| Tungsten halogen SE twin filament lamp type CP30 1250/1250W 240V (GX38q base) 3200K |
| Tungsten halogen SE twin filament lamp type CP58 1250/2500W 230V (GX38q base) 3200K |
| Tungsten halogen SE twin filament lamp type CP58 1250/2500W 240V (GX38q base) 3200K |
| Tungsten halogen SE twin filament lamp type CP32 2500/2500W 230V (GX38q base) 3200K |
| Tungsten halogen SE twin filament lamp type CP32 2500/2500W 240V (GX38q base) 3200K |

Tungsten halogen DE (double ended) lamps, R7s base

| |
|--|
| Tungsten halogen DE linear lamp type K9 300W 230V (R7s base, MOL 119mm) 3200K |
| Tungsten halogen DE linear lamp type K1 500W 230V (R7s base, MOL 119mm) 3200K |
| Tungsten halogen DE linear lamp type K1 500W 240V (R7s base, MOL 119mm) 3200K |
| Tungsten halogen DE linear lamp type P2/10 625W 230V (R7s base, MOL 189.1mm) 3200K |
| Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K |
| Tungsten halogen DE linear lamp type P2/13 (DXX) 800W 230V (R7s base, MOL 79.4mm) 3200K |
| Tungsten halogen DE linear lamp type P2/13 (DXX) 800W 240V (R7s base, MOL 79.4mm) 3200K |
| Tungsten halogen DE linear lamp type P2/11 (EME) 800W 230V (R7s base, MOL 119mm) 3200K |
| Tungsten halogen DE linear lamp type P2/11 (EME) 800W 240V (R7s base, MOL 119mm) 3200K |
| Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 230V (R7s base, MOL 189.1mm) 3200K |
| Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K |
| Tungsten halogen DE linear lamp type P2/20 1000W 230V (R7s base, MOL 119mm) 3200K |
| Tungsten halogen DE linear lamp type P2/20 1000W 240V (R7s base, MOL 119mm) 3200K |
| Tungsten halogen DE linear lamp type P2/35 1000W 230V (R7s base, MOL 95.3mm) 3200K |
| Tungsten halogen DE linear lamp type P2/35 1000W 240V (R7s base, MOL 95.3mm) 3200K |
| Tungsten halogen DE linear lamp type P2/12 1250W 230V (R7s base, MOL 189.1mm) 3200K |
| Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K |
| Tungsten halogen DE linear lamp type P2/27 (FEX) 2000W 230V (R7s base, MOL 143.8mm) 3200K |
| Tungsten halogen DE linear lamp type P2/27 (FEX) 2000W 240V (R7s base, MOL 143.8mm) 3200K |

Daylight metal halide SE (single ended) HR (hot restrike) lamps

| | |
|-------|--|
| 42201 | HMI/MSR (Osram/Philips®) SE HR 200W lamp (GZY9.5 base) 6000K |
| 42200 | HMI/MSR (Osram/Philips®) SE HR 400W lamp (GZY9.5 base) 6000K |
| 42101 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K |
| 42108 | MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base, medium bi-post) 6000K |
| 42102 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K |
| 42203 | MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K |
| 42103 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 2500W lamp (G38 base) 6000K |
| 42104 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 4000W lamp (G38 base) 6000K |
| 42206 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 6000W lamp (GY38 base) 6000K |
| 42212 | HMI/MSR (Osram/Philips®) high-efficiency SE HR 12000W lamp (GY38 base) 6000K |

Ceramic compact discharge SE lamps w/ UV-block

| | |
|--------|--|
| 42926 | Mastercolor CDM (Philips®) SE 150W SA/T 150/942 lamp (G12 base) 4200K |
| 42207 | Mastercolor CDM (Philips®) SE 150W SA/T 150/830 lamp (G12 base) 3000K |
| 42250 | Ceramic MSR (Philips®) SE HR 250W lamp (GZY9.5 base) 6000K |
| 5325/1 | Ceramic ST (Philips®) SE HR 250W lamp (GZY9.5 base) 3200K |

* Cennik nie jest ofertą handlową w świetle obowiązujących przepisów kodeksu handlowego.

Firma Milso zastrzega sobie prawo do zmian cen oraz asortymentu.

Nie odpowiada również za błędy w powyższym cenniku.

Cena brutto w zł. zawiera 23% podatku VAT