

## QUARTZCOLOR 2015

Nr Kat.	Artykuł	Cena brutto
		z VAT -em
		[ZŁ] *

# LED

## QuartzColor LED Fresnels

LD27630T	<b>Studio LED Fresnel 40W Tungsten MO</b> Head fitted w/ Fresnel lens Ø130mm, 5m length bare ended cable, in-line switch, built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	7 846 zł
LD27631T	<b>Studio LED Fresnel 40W Tungsten PO</b> Head fitted w/ Fresnel lens Ø130mm, 2m length bare ended cable (no switch), built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	8 853 zł
LD27630D	<b>Studio LED Fresnel 40W Daylight MO</b> Head fitted w/ Fresnel lens Ø130mm, 5m length bare ended cable, in-line switch, built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	7 846 zł
LD27631D	<b>Studio LED Fresnel 40W Daylight PO</b> Head fitted w/ Fresnel lens Ø130mm, 2m length bare ended cable (no switch), built in universal power supply (100-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	8 853 zł
	<b>Additional</b>	
28047	Gel frame Ø168mm	137 zł
28309	Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm)	314 zł
28049	Cone w/ variable aperture Ø168mm	533 zł
28106	manual "L"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket	170 zł
28048	4-leaf rotating barndoor Ø168mm	373 zł
28837	8-leaf rotating barndoor Ø168mm	687 zł
82012P	Small C-clamp w/ 16mm (5/8") spigot	162 zł
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
28152	Accessory safety bond (Ø2mm, length 40cm)	88 zł
LD27640T	<b>Studio LED Fresnel 90W Tungsten MO</b> Head fitted w/ Fresnel lens Ø130mm, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot Supplied w/ gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	10 062 zł



LD27642T	<b>Studio LED Fresnel 90W Tungsten PO</b>	10 451 zł
	<b>Head fitted w/</b> Fresnel lens Ø130mm, 2m length bare ended cable ( <u>no switch</u> ), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1½") spigot	
	<b>Supplied w/</b> gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	
LD27640T/1	<b>Retrofit kit 90W Tungsten for Bambino1KW</b>	7 644 zł
	<b>Base composed w/</b> 90W tungsten led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors	
	<b>Supplied w/</b> upgrade label kit	
LD27640D	<b>Studio LED Fresnel 90W Daylight MO</b>	10 062 zł
	<b>Head fitted w/</b> Fresnel lens Ø130mm, 5m length bare ended cable, in-line <u>switch</u> , built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1½") spigot	
	<b>Supplied w/</b> gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	
LD27642D	<b>Studio LED Fresnel 90W Daylight PO</b>	10 451 zł
	<b>Head fitted w/</b> Fresnel lens Ø130mm, 2m length bare ended cable ( <u>no switch</u> ), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1½") spigot	
	<b>Supplied w/</b> gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	
LD27640D/1	<b>Retrofit kit 90W Daylight for Bambino1KW</b>	7 644 zł
	<b>Base composed w/</b> 90W daylight led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors	
	<b>Supplied w/</b> upgrade label kit	
	<b>Additional</b>	
28849	Gel frame Ø198mm	158 zł
28844	Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm)	357 zł
28840	Cone w/ variable aperture Ø200mm	687 zł
28846	4-leaf rotating barndoor Ø200mm	417 zł
28847	8-leaf rotating barndoor Ø200mm	634 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł
28152	Accessory safety bond (Ø2mm, length 40cm)	88 zł
LD27250T	<b>Studio LED Fresnel 120W Tungsten MO</b>	11 224 zł
	<b>Head fitted w/</b> Fresnel lens Ø175mm, 5m length bare ended cable, in-line <u>switch</u> , built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1½") spigot	
	<b>Supplied w/</b> stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm	
LD27252T	<b>Studio LED Fresnel 120W Tungsten PO</b>	11 612 zł
	<b>Head fitted w/</b> Fresnel lens Ø175mm, 2m length bare ended cable ( <u>no switch</u> ), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan & Tilt) w/ 28mm (1½") spigot	
	<b>Supplied w/</b> stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm	
LD27252T/1	<b>Retrofit kit 120W Tungsten for Studio1KW</b>	7 980 zł
	<b>Base composed w/</b> 120W tungsten led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic display, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors	
	<b>Supplied w/</b> upgrade label kit	

LD27250D	<b>Studio LED Fresnel 120W Daylight MO</b>	11 224 zł
	<p><b>Head fitted w/</b> Fresnel lens Ø175mm, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm</p>	
LD27252D	<b>Studio LED Fresnel 120W Daylight PO</b>	11 612 zł
	<p><b>Head fitted w/</b> Fresnel lens Ø175mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan &amp; Tilt) w/ 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> stainless steel wire guard, gel frame Ø258mm, 4-leaf rotating barndoor Ø269mm</p>	
LD27252D/1	<b>Retrofit kit 120W Daylight for Studio1KW</b>	7 980 zł
	<p><b>Base composed w/</b> 120W daylight led source, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors</p> <p><b>Supplied w/</b> upgrade label kit</p>	
	<b>Additional</b>	
28859	Gel frame Ø258mm	170 zł
28304	Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm)	506 zł
28850	Cone w/ variable aperture Ø269mm	714 zł
28050	4-leaf rotating barndoor Ø269mm	426 zł
28857	8-leaf rotating barndoor Ø269mm	751 zł
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
28151	Accessory safety bond (Ø2mm, length 50cm)	88 zł
LD27260T	<b>Studio LED Fresnel 200W Tungsten MO</b>	0 zł
	<p><b>Head fitted w/</b> Fresnel lens Ø250mm, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p>	
LD27262T	<b>Studio LED Fresnel 200W Tungsten PO</b>	0 zł
	<p><b>Head fitted w/</b> Fresnel lens Ø250mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan &amp; Tilt) w/ 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p>	
LD27262T/1	<b>Retrofit kit 200W Tungsten for Studio 2KW</b>	0 zł
	<p><b>Base composed w/</b> 200W tungsten led source, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors</p> <p><b>Supplied w/</b> upgrade label kit</p>	
LD27260D	<b>Studio LED Fresnel 200W Daylight MO</b>	0 zł
	<p><b>Head fitted w/</b> Fresnel lens Ø250mm, 5m length bare ended cable, in-line <u>switch</u>, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, manual stirrup with 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p>	
LD27262D	<b>Studio LED Fresnel 200W Daylight PO</b>	0 zł
	<p><b>Head fitted w/</b> Fresnel lens Ø250mm, 2m length bare ended cable (<u>no switch</u>), built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors, Pole Operated stirrup (Pan &amp; Tilt) w/ 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> stainless steel wire guard, gel frame Ø323mm, 4-leaf rotating barndoor Ø323mm</p>	

LD27262D/1

**Retrofit kit 200W Daylight for Studio 2KW**

0 zł



**Base composed w/** 200W daylight led source, 5m length bare ended cable, in-line switch, built in universal power supply (90-240V, 50/60Hz), electronic dimming 16 bit, LCD graphic disply, internal sensor temperature, on board dimming, USB port, RDM-DMX in/out connectors

**Supplied w/** upgrade label kit

**Additional**

28093	Gel frame Ø323mm	224 zł
28306	Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)	571 zł
28090	Cone small aperture Ø323mm	400 zł
28091	Cone medium aperture Ø323mm	400 zł
28092	Cone large aperture Ø323mm	400 zł
28070	4-leaf rotating barndoor Ø323mm	586 zł
28071	8-leaf rotating barndoor Ø323mm	836 zł
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
28150	Accessory safety bond (Ø2mm, length 70cm)	88 zł

**Open face floodlights****QuartzColor Pinza**

21010	<b>Pinza 500W floodlight 230-240V</b>	712 zł
-------	---------------------------------------	--------

**Head fitted w/** On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

**Supplied w/** clamp on flexible arm

21012	<b>Black Pinza 500W floodlight 230-240V</b>	
-------	---	--

**Head fitted w/** black painted housing, On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

**Supplied w/** clamp on flexible arm

21011	<b>Pinza 500W floodlight 230-240V w/ barndoor</b>	1 199 zł
-------	---	----------

**Head fitted w/** On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

**Supplied w/** direct mount complete barndoor set + clamp on flexible arm

21013	<b>Black Pinza 500W floodlight 230-240V w/ barndoor</b>	1 199 zł
-------	---	----------

**Head fitted w/** black painted housing, On/Off in-line rocker switch 10A/250V and 4m length bare ended cable

**Supplied w/** direct mount complete barndoor set + clamp on flexible arm

**Additional**

Incandescent (Argaphoto) lamp type P2/1 500W 230V (E27 base) 3200K

Incandescent (Argaphoto) lamp type P2/1 500W 240V (E27 base) 3200K

28023	Direct mount wire mesh safety guard 3 x 3mm Ø166mm	192 zł
28021	Accessory holder Ø192mm	318 zł
28019	Wire mesh safety guard 3 x 3mm (to be used w/ 28021)	121 zł
28302	Scrim set 4 pieces (full single + full double + half single + half double; Ø192mm)	357 zł
28122	Barndoor adapter w/ wire mesh safety guard 3 x 3mm	230 zł
28022	4-leaf barndoor Ø164mm (to be used w/ 28021 or 28122)	318 zł
28120	Direct mount complete barndoor set (28122 + 28022)	450 zł

**QuartzColor Redhead**

**For Redheads kits**, see separate price list



27157	<b>Redhead 800W variable beam floodlight 230-240V</b>	1 172 zł
-------	---	----------

**Head fitted w/** On/Off in-line rocker switch 10A/250V, 4m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket

**Supplied w/** rotating barndoor adapter w/ wire mesh safety guard 3 x 3mm + 4-leaf barndoor Ø164mm

27130	<b>Redhead 800W variable beam floodlight 230-240V w/ accessory holder</b>	1 412 zł
-------	---	----------

**Head fitted w/** On/Off in-line toggle switch 10A/250V, 4m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket

**Supplied w/** rotating accessory holder Ø192mm + wire mesh safety guard 3 x 3mm + 4-leaf barndoor Ø164mm

27158	<b>Redhead 1000W variable beam floodlight 230-240V</b> <b>Head fitted w/</b> On/Off in-line toggle switch 10A/250V, 4m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket <b>Supplied w/</b> barndoor adapter w/ wire mesh safety guard 3 x 3mm + 4-leaf barndoor Ø164mm	1 199 zł
<b>Additional for Redhead</b>		
	Tungsten halogen DE linear lamp type P2/13 (DXX) 800W 230V (R7s base, MOL 79.4mm) 3200K	
	Tungsten halogen DE linear lamp type P2/13 (DXX) 800W 240V (R7s base, MOL 79.4mm) 3200K	
	Tungsten halogen DE linear lamp type P2/35 1000W 230V (R7s base, MOL 95.3mm) 3200K	
	Tungsten halogen DE linear lamp type P2/35 1000W 240V (R7s base, MOL 95.3mm) 3200K	
28023	Direct mount wire mesh safety guard 3 x 3mm Ø166mm	192 zł
28021	Rotating accessory holder Ø192mm	318 zł
28019	Wire mesh safety guard 3 x 3mm (to be used w/ 28021)	121 zł
28024	Mounted safety glass Ø192mm (to be used w/ 28021)	148 zł
28025	Mounted Dichroic filter Ø192mm (to be used w/ 28021)	724 zł
28122	Rotating barndoor adapter w/ wire mesh safety guard 3 x 3mm	230 zł
28022	4-leaf barndoor Ø164mm (to be used w/ 28021 or 28122)	318 zł
28120	Direct mount complete barndoor set (28122 + 28022)	450 zł
28302	Scrim set 4 pieces (full single + full double + half single + half double; Ø192mm)	357 zł
28602	Softbox <b>V+</b> (40 x 55 cm), to be used w/ 28600	1 468 zł
28600	Mounting device for softbox <b>V+</b> 40 x 55 cm (for 28602)	780 zł
28603	Softbox <b>V+</b> (40 x 55 cm) + Redhead mounting device (28602 + 28600)	2 248 zł
82610	Small clamp w/ 16mm (5/8") spigot	112 zł






## QuartzColor Blonde







For Blonde kits, see separate price list

21100	<b>Blonde 2000W variable beam floodlight 230-240V</b> <b>Head fitted w/</b> On/Off in-line toggle switch 20A/250V, 5.5m length bare ended cable, integrated accessory holder, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted <b>Supplied w/</b> wire mesh safety guard 3 x 3mm + 4-leaf rotating barndoor Ø269mm	2 477 zł
21101	<b>Black Blonde 2000W variable beam floodlight 230-240V</b> <b>Head fitted w/</b> black painted housing, On/Off in-line toggle switch 20A/250V, 5.5m length bare ended cable, integrated accessory holder, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted <b>Supplied w/</b> wire mesh safety guard 3 x 3mm + 4-leaf rotating barndoor Ø269mm	2 583 zł
<b>Additional for Black Blonde</b>		
	Tungsten halogen DE linear lamp type P2/27 (FEX) 2000W 230V (R7s base, MOL 143.8mm) 3200K	
	Tungsten halogen DE linear lamp type P2/27 (FEX) 2000W 240V (R7s base, MOL 143.8mm) 3200K	
28051	Direct mount wire mesh safety guard 3 x 3mm Ø253.6mm	247 zł
28304	Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm)	506 zł
28053	Mounted safety glass Ø258mm	379 zł
28054	Mounted Dichroic filter Ø258mm	1 369 zł
28050	4-leaf rotating barndoor Ø269mm	426 zł
28612	Softbox <b>V+</b> (90 x 120 cm) w/ 3 front diffuser screens	3 536 zł
28610	Ring Ø270mm (for 28612)	1 904 zł
28613	Softbox <b>V+</b> (90 x 120 cm) + ring Ø270mm (28612 + 28610)	5 440 zł
82610	Small clamp w/ 16mm (5/8") spigot	112 zł
82012P	Small C-clamp w/ 16mm (5/8") spigot	162 zł
28152	Accessory safety bond (Ø2mm, length 40cm)	88 zł

## Tungsten spotlights QuartzColor Bambino Fresnels

For Bambino kits (500/300 & 650/500W), see separate price list

27620		<b>Bambino Fresnel 500/300W MO 230-240V w/ "U"-shape stirrup</b>	<b>1 918 zł</b>
		<b>Head fitted w/</b> Proprietary Fresnel lens Ø90mm, On/Off in-line rocker switch 10A/250V, 4m length bare ended cable and manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted <b>Supplied w/</b> gel frame Ø110mm + 4-leaf rotating barndoor Ø110mm	
		<b>Additional</b>	
		Tungsten halogen SE lamp type CP81 (FMF) <b>300W</b> 230V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP81 (FSK) 300W 240V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP82 (FRH) <b>500W</b> 230V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP82 (FRJ) 500W 240V (GY9.5 base, oriented 2-pin) 3200K	
28080		Gel frame Ø110mm (not for 120V products)	<b>80 zł</b>
28301		Scrim set 4 pieces (full single + full double + half single + half double; Ø110mm)	<b>256 zł</b>
28104		Cone w/ variable aperture Ø110mm	<b>309 zł</b>
28105		manual "L"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket	<b>160 zł</b>
28040		4-leaf rotating barndoor Ø110mm (not for 120V products)	<b>240 zł</b>
82012P		Small C-clamp w/ 16mm (5/8") spigot	<b>162 zł</b>
28152		Accessory safety bond (Ø2mm, length 40cm)	<b>88 zł</b>
27630		<b>Bambino Fresnel 650/500W MO 230-240V w/ "U"-shape stirrup</b>	<b>2 237 zł</b>
		<b>Head fitted w/</b> Fresnel lens Ø130mm, On/Off in-line rocker switch 10A/250V, 4m length bare ended cable and manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted <b>Supplied w/</b> gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm	
27631		<b>Bambino Fresnel 650/500W PO 230-240V</b>	<b>3 622 zł</b>
		<b>Head fitted w/</b> Fresnel lens Ø130mm, On/Off head mounted toggle switch 8A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot <b>Supplied w/</b> gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm	
		<b>Additional</b>	
		Tungsten halogen SE lamp type CP81 (FMF) <b>300W</b> 230V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP81 (FSK) 300W 240V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP82 (FRH) <b>500W</b> 230V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP82 (FRJ) 500W 240V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP89 (FRL) <b>650W</b> 230V (GY9.5 base, oriented 2-pin) 3200K	
		Tungsten halogen SE lamp type CP89 (FRM) 650W 240V (GY9.5 base, oriented 2-pin) 3200K	
28047		Gel frame Ø168mm	<b>137 zł</b>
28309		Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm)	<b>314 zł</b>
28049		Cone w/ variable aperture Ø168mm	<b>533 zł</b>
28106		manual "L"-shape stirrup w/ single lock-off knob and integrated 16mm (5/8") socket	<b>170 zł</b>
28048		4-leaf rotating barndoor Ø168mm	<b>373 zł</b>
28837		8-leaf rotating barndoor Ø168mm	<b>687 zł</b>
82012P		Small C-clamp w/ 16mm (5/8") spigot	<b>162 zł</b>
82013		Hook clamp w/ 28mm (1 1/8") socket	<b>439 zł</b>
28152		Accessory safety bond (Ø2mm, length 40cm)	<b>88 zł</b>
27640		<b>Bambino Fresnel 1kW MO Mk2 230-240V</b>	<b>3 047 zł</b>
		<b>Head fitted w/</b> Fresnel lens Ø130mm, On/Off in-line rocker switch 15A/250V, 5m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1 1/8") spigot <b>Supplied w/</b> gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	
27642		<b>Bambino Fresnel 1kW PO Mk2 230-240V</b>	<b>4 075 zł</b>
		<b>Head fitted w/</b> Fresnel lens Ø130mm, On/Off head mounted toggle switch 8A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot <b>Supplied w/</b> gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm	
		<b>Additional</b>	
		Tungsten halogen SE lamp type CP40 (FKJ) 1000W 230V (G22 base, medium bi-post) 3200K	
		Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K	



28849	Gel frame Ø198mm	158 zł
28844	Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm)	357 zł
28840	Cone w/ variable aperture Ø200mm	687 zł
28846	4-leaf rotating barndoor Ø200mm	417 zł
28847	8-leaf rotating barndoor Ø200mm	634 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł
28152	Accessory safety bond (Ø2mm, length 40cm)	88 zł
	<b>27650 Bambino Fresnel 2kW MO Mk2 230-240V</b> <b>Head fitted w/</b> Fresnel lens Ø175mm, On/Off <u>head mounted</u> toggle switch 20A/250V, 5m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spigot <b>Supplied w/</b> gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm	3 995 zł
	<b>27652 Bambino Fresnel 2kW PO Mk2 230-240V</b> <b>Head fitted w/</b> Fresnel lens Ø175mm, On/Off <u>head mounted</u> toggle switch 20A/250V, 2m length bare ended cable, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spigot <b>Supplied w/</b> gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm	4 794 zł
	<b>Additionalis</b>	
	Tungsten halogen SE lamp type CP41 (FKK) 2000W 230V (G38 base, mogul bi-post) 3200K	
	Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K	
28859	Gel frame Ø258mm	170 zł
28304	Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm)	506 zł
28850	Cone w/ variable aperture Ø269mm	714 zł
28050	4-leaf rotating barndoor Ø269mm	426 zł
28857	8-leaf rotating barndoor Ø269mm	751 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł
28151	Accessory safety bond (Ø2mm, length 50cm)	88 zł
	<b>27660 Bambino Fresnel 5kW MO Mk2 230-240V</b> <b>Head fitted w/</b> Fresnel lens Ø250mm, On/Off <u>head mounted</u> toggle switch 60A/250V, 5m length bare ended cable and manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot <b>Supplied w/</b> gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm	5 566 zł
	<b>27662 Bambino Fresnel 5kW PO Mk2 230-240V</b> <b>Head fitted w/</b> Fresnel lens Ø250mm, On/Off <u>head mounted</u> toggle switch 60A/250V, 2m length bare ended cable, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) stirrup w/ 28mm (1½") spigot <b>Supplied w/</b> gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm	6 232 zł
	<b>Additionalis</b>	
	Tungsten halogen SE lamp type CP29 5000W 230V (G38 base, mogul bi-post) 3200K	
	Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K	
28093	Gel frame Ø323mm	224 zł
28306	Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)	571 zł
28090	Cone small aperture Ø323mm	400 zł
28091	Cone medium aperture Ø323mm	400 zł
28092	Cone large aperture Ø323mm	400 zł
28070	4-leaf rotating barndoor Ø323mm	586 zł
28071	8-leaf rotating barndoor Ø323mm	836 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł
28150	Accessory safety bond (Ø2mm, length 70cm)	88 zł
	<b>27680 Bambino Fresnel 10kW MO Mk2 230-240V</b> <b>Head fitted w/</b> Fresnel lens Ø350mm, On/Off <u>head mounted</u> rotary switch 125A/250V, 5m length bare ended cable and manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot <b>Supplied w/</b> gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm	0 zł
	<b>27682 Bambino Fresnel 10kW PO Mk2 230-240V</b> <b>Head fitted w/</b> Fresnel lens Ø350mm, On/Off <u>head mounted</u> rotary switch 125A/250V, 2m length bare ended cable, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spigot <b>Supplied w/</b> gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm	0 zł
	<b>Additionalis</b>	
	Tungsten halogen SE lamp type CP83 10000W 230V (G38 base, mogul bi-post) 3200K	
	Tungsten halogen SE lamp type CP83 10000W 240V (G38 base, mogul bi-post) 3200K	

28097	Gel frame Ø408mm	250 zł
28307	Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm)	818 zł
28094	Cone small aperture Ø401mm	618 zł
28095	Cone small medium Ø401mm	618 zł
28096	Cone large aperture Ø401mm	618 zł
28074	4-leaf rotating barndoor Ø401mm	664 zł
28075	8-leaf rotating barndoor Ø401mm	879 zł
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
82002	Safety cable 50kg (Ø4mm, length 70cm)	277 zł

## QuartzColor Studio Fresnels

	27250	<b>Studio Fresnel 1kW MO Mk2 230-240V</b> Head fitted w/ Fresnel lens Ø175mm, On/Off head mounted toggle switch 8A/250V, 5m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1 1/8") socket Supplied w/ gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm	3 356 zł
	27250S1	<b>Special version w/o switch</b> , 2m length bare ended cable	3 249 zł
	27252	<b>Studio Fresnel 1kW PO Mk2 230-240V</b> Head fitted w/ Fresnel lens Ø175mm, On/Off head mounted toggle switch 80A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") socket Supplied w/ gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm	4 315 zł
	27252S1	<b>Special version w/o switch</b> , 2m length bare ended cable	4 208 zł
		<b>Additional</b> Tungsten halogen SE lamp type CP40 (FKJ) 1000W 230V (G22 base, medium bi-post) 3200K Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K	
	28859	Gel frame Ø258mm	170 zł
	28304	Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm)	506 zł
	28850	Cone w/ variable aperture Ø269mm	714 zł
	28050	4-leaf rotating barndoor Ø269mm	426 zł
	28857	8-leaf rotating barndoor Ø269mm	751 zł
	82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
	28151	Accessory safety bond (Ø2mm, length 50cm)	88 zł
	27260	<b>Studio Fresnel 2kW MO Mk2 230-240V</b> Head fitted w/ Fresnel lens Ø250mm, On/Off head mounted toggle switch 16A/250V, 5m length bare ended cable, manual "U"-shape stirrup w/ single lock-off knob and 28mm (1 1/8") socket Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm	4 821 zł
	27260S1	<b>Special version w/o switch</b> , 2m length bare ended cable	4 688 zł
	27262	<b>Studio Fresnel 2kW PO Mk2 230-240V</b> Head fitted w/ Fresnel lens Ø250mm, On/Off head mounted toggle switch 16A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") socket Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm	5 716 zł
	27262S1	<b>Special version w/o switch</b> , 2m length bare ended cable	5 471 zł
	27262S2	<b>Special version with On/Off head mounted rotary switch 16A/250V</b> , 2m length bare ended cable	5 966 zł
		<b>Additional</b> Tungsten halogen SE lamp type CP41 (FKK) 2000W 230V (G38 base, mogul bi-post) 3200K Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K	
	28093	Gel frame Ø323mm	224 zł
	28306	Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)	571 zł
	28090	Cone small aperture Ø323mm	400 zł
	28091	Cone medium aperture Ø323mm	400 zł
	28092	Cone large aperture Ø323mm	400 zł
	28070	4-leaf rotating barndoor Ø323mm	586 zł
	28071	8-leaf rotating barndoor Ø323mm	836 zł
	82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
	28150	Accessory safety bond (Ø2mm, length 70cm)	88 zł



	27270	<b>Studio Fresnel 5kW MO Mk2 230-240V</b> Head fitted w/ Fresnel lens Ø300mm, On/Off head mounted rotary switch 45A/250V, 5m length bare ended cable, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm	0 zł
	27270S1	<b>Special version w/o switch</b> , 2m length bare ended cable	0 zł
	27272	<b>Studio Fresnel 5kW PO Mk2 230-240V</b> Head fitted w/ Fresnel lens Ø300mm, On/Off head mounted rotary switch 45A/250V, 2m length bare ended cable, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm	0 zł
	27272S1	<b>Special version w/o switch</b> , 2m length bare ended cable	0 zł
		<b>Additional</b> Tungsten halogen SE lamp type CP29 5000W 230V (G38 base, mogul bi-post) 3200K Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K	
	28097	Gel frame Ø408mm	250 zł
	28307	Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm)	818 zł
	28094	Cone small aperture Ø401mm	618 zł
	28095	Cone small medium Ø401mm	618 zł
	28096	Cone large aperture Ø401mm	618 zł
	28074	4-leaf rotating barndoor Ø401mm	664 zł
	28075	8-leaf rotating barndoor Ø401mm	879 zł
	82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
	82002	Safety cable 50kg (Ø4mm, length 70cm)	277 zł

## QuartzColor Tungsten Pars

	27940	<b>Tungsten Par 1kW MO 230-240V w/o switch</b> Head fitted w/ 7m length bare ended cable (no switch), full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot	0 zł
	27941	<b>Tungsten Par 1kW MO 230-240V</b> Head fitted w/ On/Off in-line toggle switch 15A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm	0 zł
		<b>Additional</b> Tungsten halogen SE lamp type CP40 (FKJ) 1000W 230V (G22 base, medium bi-post) 3200K Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K	
	28093	Gel frame Ø323mm	224 zł
	28306	Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)	571 zł
	28114	4-leaf rotating barndoor Ø323mm	510 zł
	28071	8-leaf rotating barndoor Ø323mm	836 zł
	28341	Mounted spot lens Ø250mm, black handle	932 zł
	28342	Mounted medium flood lens Ø250mm, green handle	932 zł
	28343	Mounted wide flood lens Ø250mm, yellow handle	932 zł
	28344	Mounted extra-wide flood lens Ø250mm, red handle	932 zł
	28345	Mounted frosted Fresnel lens Ø250mm, white handle	879 zł
	28848	Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel: Ø250mm)	4 384 zł
	28814	Carrying case for 5 lenses Ø250mm (for HMI Par 1.2kW, OneLight™ HMI Par 1.2kW & Tungsten Par 1kW); 38 x 43 x 42cm (ext. dim. L x W x H) weight (empty) 7kg	
	28806	Complete diffusion lens set Ø250mm w/ carrying case (28848 + 28814)	5 832 zł
	82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
	82002	Safety cable 50kg (Ø4mm, length 70cm)	277 zł
	27950	<b>Tungsten Par 2kW MO 230-240V w/o switch</b> Head fitted w/ 7m length bare ended cable (no switch), full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot	0 zł
	27951	<b>Tungsten Par 2kW MO 230-240V</b> Head fitted w/ On/Off in-line toggle switch 20A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") spigot Supplied w/ gel frame Ø400mm + 4-leaf rotating barndoor Ø401mm	0 zł

**Additional**

Tungsten halogen SE lamp type CP41 (FKK) 2000W 230V (G38 base, mogul bi-post) 3200K

Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K

28097	Gel frame Ø408mm	250 zł
28307	Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm)	818 zł
28115	4-leaf rotating barndoor Ø401mm	647 zł
28075	8-leaf rotating barndoor Ø401mm	879 zł
28441	Mounted spot lens Ø350mm, black handle	1 604 zł
28442	Mounted medium flood lens Ø350mm, green handle	1 604 zł
28443	Mounted wide flood lens Ø350mm, yellow handle	1 604 zł
28444	Mounted extra-wide flood lens Ø350mm, red handle	1 604 zł
28445	Mounted frosted Fresnel lens Ø350mm, white handle	1 907 zł
28868	Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø350mm)	8 021 zł
28812	Carrying case for 5 lenses Ø350mm (for HMI Par 4/2.5kW & Tungsten Par 2kW); 48 x 39 x 49cm (ext. dim. L x W x H), weight (empty) 11kg	1 454 zł
28808	Complete diffusion lens set Ø350mm w/ carrying case (28868 + 28812)	9 464 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł
82002	Safety cable 50kg (Ø4mm, length 70cm)	277 zł

27930 **Tungsten Par 5kW MO 230-240V w/o switch** 0 zł  
**Head fitted w/** 7m length bare ended cable (no switch), full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot

27933 **Tungsten Par 5kW MO 230-240V** 0 zł  
**Head fitted w/** On/Off head mounted toggle switch 60A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot  
**Supplied w/** gel frame Ø546mm + 4-leaf rotating barndoor Ø546mm

**Additional**

Tungsten halogen SE lamp type CP29 5000W 230V (G38 base, mogul bi-post) 3200K

Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K

28889	Gel frame Ø546mm	450 zł
28884	Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm)	2 480 zł
28886	4-leaf rotating barndoor Ø546mm	2 015 zł
28541	Mounted spot lens Ø450mm, black handle	2 312 zł
28542	Mounted medium flood lens Ø450mm, green handle	2 312 zł
28543	Mounted wide flood lens Ø450mm, yellow handle	2 312 zł
28544	Mounted extra-wide flood lens Ø450mm, red handle	2 312 zł
28545	Mounted frosted Fresnel lens Ø450mm, white handle	4 219 zł
28888	Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm)	10 920 zł
28813	Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg	2 930 zł
28810	Complete diffusion lens set Ø450mm w/ carrying case (28888 + 28813)	13 477 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł
82002	Safety cable 50kg (Ø4mm, length 70cm)	277 zł

27961 **Tungsten Par 10kW MO 230-240V** 0 zł  
**Head fitted w/** On/Off head mounted toggle switch 60A/250V, 7m length bare ended cable, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot  
**Supplied w/** gel frame Ø546mm + 4-leaf rotating barndoor Ø546mm

**Additional**

Tungsten halogen SE lamp type CP29 10000W 230V (G38 base, mogul bi-post) 3200K

Tungsten halogen SE lamp type CP29 10000W 240V (G38 base, mogul bi-post) 3200K

28889	Gel frame Ø546mm	450 zł
28884	Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm)	2 480 zł
28886	4-leaf rotating barndoor Ø546mm	2 015 zł
28541	Mounted spot lens Ø450mm, black handle	2 312 zł
28542	Mounted medium flood lens Ø450mm, green handle	2 312 zł
28543	Mounted wide flood lens Ø450mm, yellow handle	2 312 zł
28544	Mounted extra-wide flood lens Ø450mm, red handle	2 312 zł
28545	Mounted frosted Fresnel lens Ø450mm, white handle	4 219 zł
28888	Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm)	10 920 zł
28813	Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg	2 930 zł
28810	Complete diffusion lens set Ø450mm w/ carrying case (28888 + 28813)	13 477 zł
		0 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł

82002	Safety cable 50kg (Ø4mm, length 70cm)	277 zł
-------	---------------------------------------	--------

## Fill softlights QuartzColor Arturo

	26500	<b>Arturo 1 (1250W) softlight MO 230-240V</b> <b>Head one light-one circuit fitted w/</b> On/Off in-line toggle switch 8A/250V, 5m length bare ended cable, bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spiaot <b>Supplied w/</b> gel frame 400 x 230mm	3 622 zł
	26510	<b>Arturo 1 (1250W) softlight PO 230-240V</b> <b>Head one light-one circuit fitted w/</b> On/Off in-line toggle switch 8A/250V, 5m length bare ended cable, bottom skid, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spiaot <b>Supplied w/</b> gel frame 400 x 230mm	3 958 zł
<b>Additionalis</b>			
Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K			
28312	Gel frame 400 x 230mm		293 zł
28310	Egg-crate narrow 400 x 230mm		1 012 zł
28311	Egg-crate standard 400 x 230mm		1 012 zł
82013	Hook clamp w/ 28mm (1½") socket		439 zł
	26520	<b>Arturo 2 (2500/1250W) softlight MO 230-240V</b> <b>Head two lights-two circuits fitted w/</b> On/Off <u>head mounted</u> rotary <i>select</i> switch 45A/250V, 5m length bare ended cable, bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spiaot <b>Supplied w/</b> gel frame 512 x 310mm	4 799 zł
	26530	<b>Arturo 2 (2500/1250W) softlight PO 230-240V</b> <b>Head two lights-two circuits fitted w/</b> On/Off <u>head mounted</u> rotary <i>select</i> switch 45A/250V, 5m length bare ended cable, bottom skid, <u>Pole Operated</u> "U"-shape stirrup (Pan & Tilt) w/ 28mm (1½") spiaot <b>Supplied w/</b> gel frame 512 x 310mm	6 339 zł
<b>Additionalis</b>			
Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K			
Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K			
28315	Gel frame 512 x 310mm		346 zł
28313	Egg-crate narrow 512 x 310mm		1 113 zł
28314	Egg-crate standard 512 x 310mm		1 113 zł
82013	Hook clamp w/ 28mm (1½") socket		439 zł
26540	<b>Arturo 4 (5000/2500W) softlight MO 230-240V</b> <b>Head four lights-four circuits fitted w/</b> On/Off <u>head mounted</u> rotary <i>select</i> switch 45A/250V, 5m length bare ended cable, bottom skid, manual "U"-shape square base stirrup w/ single lock-off knob and 28mm (1½") spiaot <b>Supplied w/</b> gel frame 610 x 405mm		7 180 zł

26550	<b>Arturo 4 (5000/2500W) softlight PO 230-240V</b> Head four lights-four circuits fitted w/ On/Off head mounted rotary select switch 45A/250V, 5m length bare ended cable, bottom skid, Pole Operated "U"-shape stirrup (Pan & Tilt) w/ 28mm (1 1/8") spigot Supplied w/ gel frame 610 x 405mm	7 926 zł
<b>Additional</b>		
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K	
28318	Gel frame 610 x 405mm	405 zł
28316	Egg-crate narrow 610 x 405mm	1 204 zł
28317	Egg-crate standard 610 x 405mm	1 204 zł
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł

## QuartzColor Iadi Fill

For Iadi kits, see separate price list

26020	<b>Iadi Fill 1kW floodlight 230-240V</b> Head fitted w/ On/Off in-line toggle switch 8A/250V, 4m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted <b>Integrated accessories:</b> 4-leaf barndoor + wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener	0 zł
<b>Additional</b>		
	Tungsten halogen DE linear lamp type K9 <b>300W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type K1 <b>500W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type K1 500W 240V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/11 (EME) <b>800W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/11 (EME) 800W 240V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/20 <b>1000W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/20 1000W 240V (R7s base, MOL 119mm) 3200K	
28005	Scrim full single, frame size 176 x 135mm (W x H), w/ quick release fastener	285 zł
28004	Scrim full double, frame size 176 x 135mm (W x H), w/ quick release fastener	285 zł
28006	Mounted Dichroic filter (daylight), frame size 176 x 135mm (W x H), w/ quick release fastener	796 zł
28007	Mounted diffuser filter (opal glass), frame size 176 x 135mm (W x H), w/ quick release fastener	472 zł
28003	Set of 4 intensifying panels for Iadi barndoors	346 zł
82610	Small clamp w/ 16mm (5/8") spigot	112 zł
82012P	Small C-clamp w/ 16mm (5/8") spigot	162 zł

## QuartzColor Ghost

27771	<b>Ghost 5kW suspended fill light 230-240V</b> Main body fitted w/ 2m length bare ended cable (no switch), 28mm (1 1/8") spigot for overhead suspension and safety bond <b>Supplied accessory on each compartment:</b> wire mesh safety guard 3 x 3mm (239.5 x 114.5mm)	4 664 zł
<b>Additional</b>		
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K	
28100	White diffuser cone Ø800mm x 1m length (supplied complete w/ 2 integrated support rings)	1 257 zł
28200	Black (spot) diffuser cone Ø800mm x 1m length (supplied complete w/ 2 integrated support rings)	0 zł
28200FB	Black top/white bottom diffuser cone Ø800mm x 1m length (supplied complete w/ 2 integrated support rings)	0 zł

28500	White (soft) diffuser cone Ø800mm x 1m length (fits onto the two support rings via Velcro straps, to be ordered separately, see 28501)	0 zł
28501	Two support rings (to be used w/ 28200, 28200FB & 28500)	527 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł

## Cyclorama softlights QuartzColor Iris

26070	<p><b>Iris 1 (1250W) Cyclorama MO 230-240V</b>  <b>Head one light-one circuit fitted w/</b> 5m length bare ended cable (no switch), manual "U"-shape flat base stirrup w/ single lock-off knob, lateral assembly plates and 28mm (1½") socket  <b>Integrated accessories:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm</p>	2 317 zł
26080	<p><b>Iris 1 (1250W) Cyclorama PO 230-240V</b>  <b>Head one light-one circuit fitted w/</b> 5m length bare ended cable (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates, 28mm (1½") socket  <b>Integrated accessories:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm</p> <p><b>Additional</b></p> <p>Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K</p>	2 637 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł
26100	<p><b>Iris 2 (1250W x2) vertical Cyclorama PO 230-240V</b>  <b>Head two lights-two circuits fitted w/</b> 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1½") socket  <b>Integrated accessories on each compartment:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm</p>	4 821 zł
26110	<p><b>Iris 2 (1250W x2) horizontal Cyclorama PO 230-240V</b>  <b>Head two lights-two circuits fitted w/</b> 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1½") socket  <b>Integrated accessories on each compartment:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm</p>	4 821 zł
26090	<p><b>Iris 2 (1250W x2) vertical Cyclorama split PO 230-240V</b>  <b>Head two lights-two circuits fitted w/</b> 5m length bare ended cable on each compartment (no switch), split Pole Operated "U"-shape square base stirrup (Tilt only, limited run, 1 + 1 luminaries, see specification sheet 15006 for more details) w/ lateral assembly plates, 28mm (1½") socket  <b>Integrated accessories on each compartment:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm</p> <p><b>Additional</b></p> <p>Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K  Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K</p>	5 593 zł
82013	Hook clamp w/ 28mm (1½") socket	439 zł

26130	<b>Iris 3 (1250W x3) horizontal Cyclorama PO 230-240V</b> <b>Head</b> three lights-three circuits fitted w/ 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1 1/8") socket <b>Integrated accessories on each compartment:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm	6 658 zł
	<b>Additional</b>	
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K	
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
26150	<b>Iris 4 (1250W x4) Cyclorama PO 230-240V</b> <b>Head</b> four lights-four circuits fitted w/ 5m length bare ended cable on each compartment (no switch), Pole Operated "U"-shape square base stirrup (Tilt only) w/ lateral assembly plates. 28mm (1 1/8") socket <b>Integrated accessories on each compartment:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm	7 724 zł
26140	<b>Iris 4 (1250W x4) Cyclorama split PO 230-240V</b> <b>Head</b> four lights-four circuits fitted w/ 5m length bare ended cable on each compartment (no switch), split Pole Operated "U"-shape square base stirrup (Tilt only, limited run, 2 + 2 luminaries, see specification sheet 15011 for more details) w/ lateral assembly plates, 28mm (1 1/8") socket <b>Integrated accessories on each compartment:</b> wire mesh safety guard 3 x 3mm (400 x 298mm) + gel frame 400 x 305mm	9 189 zł
	<b>Additional</b>	
	<b>Additional for IRIS</b>	
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K	
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
26060	<b>Mini Iris (1250W) Cyclorama MO 230-240V</b> <b>Head</b> fitted w/ On/Off in-line toggle switch 8A/250V, 4m length bare ended cable, manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted <b>Integrated accessory:</b> wire mesh safety guard 3 x 3mm (260 x 182mm)	1 838 zł
	<b>Additional</b>	
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K	
28010	Extended gel frame, extension 135mm, 400 x 305mm (W x H)	490 zł
3360.170	Spare manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted (for Mini Iris Cyclorama MO)	0 zł
82013	Hook clamp w/ 28mm (1 1/8") socket	439 zł
<h2>QuartzColor Orion</h2>		
26010	<b>Orion 1 (1250W) Cyclorama 230-240V</b> <b>Head</b> fitted w/ 5m length bare ended cable (no switch) <b>Supplied w/</b> wire mesh safety guard 3 x 3mm w/ quick release fastener (260 x 182mm) + flexible gel frame 290 x 245mm	2 184 zł

Additional		
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K	
28001	Flexible gel frame 290 x 245mm	<b>218 zł</b>
26045	<b>Orion 4 (1250W x4) rigid Cyclorama Mk2 230-240V</b> Head module 1 is fitted w/ 9-pin male power input panel connector, module 4 is fitted w/ 0.8m length cable with 9-pin female in-line connector (no switch). For luminaries arrangement. see specification sheet for more details On each compartment, supplied w/ wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener + flexible gel frame 290 x 245mm	<b>8 230 zł</b>
26055	<b>Orion 4 (1250W x4) hinged Cyclorama Mk2 230-240V</b> Head module 1 is fitted w/ 9-pin male power input panel connector, module 4 is fitted w/ 0.8m length cable with 9-pin female in-line connector (no switch). For luminaries arrangement. see specification sheet for more details On each compartment, supplied w/ wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener + flexible gel frame 290 x 245mm	<b>8 470 zł</b>
Additional on next page		
Additional for ORION		
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K	
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K	
28001	Flexible gel frame 290 x 245mm	<b>218 zł</b>
28013	7m length power cable for four Orion 4	<b>2 606 zł</b>
28014	Adapter Mk1 to Mk2 for power cable 28013	<b>2 469 zł</b>



## QuartzColor Iadi Cyc

26030	<b>Iadi Cyc 1kW softlight 230-240V</b> Head fitted w/ On/Off in-line toggle switch 8A/250V, 4m length bare ended cable and manual "U"-shape flat base stirrup w/ single lock-off knob and 16mm (5/8") socket fitted  Integrated accessories: 4-leaf barndoor + wire mesh safety guard 3 x 3mm (290 x 201mm) w/ quick release fastener	<b>0 zł</b>
Additional		
	Tungsten halogen DE linear lamp type K9 <b>300W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type K1 <b>500W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type K1 500W 240V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/11 (EME) <b>800W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/11 (EME) 800W 240V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/20 <b>1000W</b> 230V (R7s base, MOL 119mm) 3200K	
	Tungsten halogen DE linear lamp type P2/20 1000W 240V (R7s base, MOL 119mm) 3200K	
28005	Scrim full single, frame size 176 x 135mm (W x H), w/ quick release fastener	<b>285 zł</b>
28004	Scrim full double, frame size 176 x 135mm (W x H), w/ quick release fastener	<b>285 zł</b>
28006	Mounted Dichroic filter (daylight), frame size 176 x 135mm (W x H), w/ quick release fastener	<b>796 zł</b>
28007	Mounted diffuser filter (opal glass), frame size 176 x 135mm (W x H), w/ quick release fastener	<b>472 zł</b>
28003	Set of 4 intensifying panels for Iadi barndoors	<b>346 zł</b>
82610	Small clamp w/ 16mm (5/8") spigot	<b>112 zł</b>
82012P	Small C-clamp w/ 16mm (5/8") spigot	<b>162 zł</b>


# Daylight standard spotlights

## QuartzColor HMI Fresnels

For HMI Fresnel **PO** versions, please contact us

	<p>27020 <b>HMI Fresnel 200W 220-240V</b>  <b>Head fitted w/</b> Fresnel lens Ø90mm, 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket  <b>Supplied w/</b> 7m length head to ballast extension cable fitted w/ male and female 7-pin Amphenol® twist lock connectors + gel frame Ø110mm + 4-leaf rotating barndoor Ø110mm</p>	<p>0 zł</p>
	<p>27021 <b>HMI Fresnel 200W 220-240V + ballast - SET</b>  <b>Head fitted w/</b> Fresnel lens Ø90mm, 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket  <b>Supplied w/</b> <u>electronic ballast 200W</u> (7-pin Amphenol® female connector) + 7m length head to ballast extension cable fitted w/ male and female 7-pin Amphenol® twist lock connectors + gel frame Ø110mm + <u>scrim set 4 pieces</u> (full single + full double + half single + half double; Ø110mm) + 4-leaf rotating barndoor Ø110mm + plywood <u>flight case</u></p>	<p>0 zł</p>
<p><b>Additional on next page</b> <b>Additional</b></p>		
<p>42201</p>	<p>HMI/MSR (Osram/Philips®) SE HR 200W lamp (GZY9.5 base) 6000K</p>	
<p>25921</p>	<p>Electronic ballast 200W (110/220V, 50/60Hz, 7-pin Amphenol® female connector) w/ auto voltage selection</p>	
<p>HMI Fresnel 200W can be used w/ other brand 200W ballast without additional adapter cable</p>		
<p>28823</p>	<p>7m head to ballast extension cable (for HMI Fresnel &amp; Par 200W) fitted w/ male and female</p>	
<p>28080</p>	<p>7-pin Amphenol® twist lock connectors (not for 120V products) Gel frame Ø110mm (not for 120V products)</p>	
<p>28301</p>	<p>Scrim set 4 pieces (full single + full double + half single + half double; Ø110mm)</p>	
<p>28104</p>	<p>Cone w/ variable aperture Ø110mm</p>	
<p>28040</p>	<p>4-leaf rotating barndoor Ø110mm (not for 120V products)</p>	
<p>28108</p>	<p>8-leaf rotating barndoor Ø110mm</p>	
<p>5320/170</p>	<p>Spare manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket (for HMI Fresnel 200W)</p>	
<p>82013</p>	<p>Hook clamp w/ 28mm (1 1/8") socket</p>	
<p>28152</p>	<p>Accessory safety bond (Ø2mm, length 40cm)</p>	
	<p>27030 <b>HMI Fresnel 400W 220-240V</b>  <b>Head fitted w/</b> Fresnel lens Ø130mm, 0.8m length cable w/ 7-pin in-line Schaultbau® male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket  <b>Supplied w/</b> 7m length head to ballast extension cable fitted w/ male and female 7-pin Schaultbau® connectors + gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm</p>	<p>0 zł</p>
	<p>27031 <b>HMI Fresnel 400W 220-240V + ballast - SET</b>  <b>Head fitted w/</b> Fresnel lens Ø130mm, 0.8m length cable w/ 7-pin in-line Schaultbau® male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket  <b>Supplied w/</b> <u>electronic ballast 400/575W</u> (7-pin Schaultbau® female connector) + 7m length head to ballast extension cable fitted w/ male and female 7-pin Schaultbau® connectors + gel frame Ø168mm + <u>scrim set 4 pieces</u> (full single + full double + half single + half double; Ø168mm) + 4-leaf rotating barndoor Ø168mm + plywood <u>flight case</u></p>	<p>0 zł</p>
<p><b>Additional</b></p>		
<p>42200</p>	<p>HMI/MSR (Osram/Philips®) SE HR 400W lamp (GZY9.5 base) 6000K</p>	
<p>25932</p>	<p>Electronic ballast 575/400W (110/220V, 50/60Hz, 7-pin Schaultbau® &amp; 7-pin Amphenol® female connectors) w/ auto voltage selection (needs adaptor for use w/ 575W QC head)</p>	
<p>HMI Fresnel 400W can be used w/ other brand 400W ballast without additional adapter cable</p>		
<p>28833</p>	<p>7m head to ballast extension cable (for HMI Fresnel 400W) fitted w/ male and female 7-pin</p>	
<p>28047</p>	<p>Schaultbau® connectors (not for 120V products) Gel frame Ø168mm</p>	
<p>28309</p>	<p>Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm)</p>	
<p>28049</p>	<p>Cone w/ variable aperture Ø168mm</p>	
<p>28048</p>	<p>4-leaf rotating barndoor Ø168mm</p>	
<p>28837</p>	<p>8-leaf rotating barndoor Ø168mm</p>	
<p>5340/170</p>	<p>Spare manual "U"-shape round base stirrup w/ single lock-off knob and 16mm (5/8") socket (for HMI Fresnel 400W)</p>	



82013	Hook clamp w/ 28mm (1½") socket	
28152	Accessory safety bond (Ø2mm, length 40cm)	
	27040	<b>HMI Fresnel 575W 220-240V</b> <span style="float: right;"><b>0 zł</b></span>
		<b>Head fitted w/</b> Fresnel lens Ø130mm, 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") spigot
		<b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm
<b>Additional</b>		
42101	HMI/MSR (Osram/Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K	
25941	Electronic ballast 575W (110/220V, 50/60Hz, 7-pin Veam® type female connector) w/ auto voltage selection	
25030	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection	
25030DMX	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control	
25220	Magnetic ballast BCS-575W/E (220-240V, 50Hz, 7-pin Veam® type female connector)	
<i>Magnetic ballast w/ DMX control on request only</i>		
28843	Adapter cable for use w/ other brand 575W ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 575W)	
28201	8m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)	
28202	15m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)	
28849	Gel frame Ø198mm	
28844	Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm)	
28840	Cone w/ variable aperture Ø200mm	
28846	4-leaf rotating barndoor Ø200mm	
28847	8-leaf rotating barndoor Ø200mm	
82013	Hook clamp w/ 28mm (1½") socket	
28151	Accessory safety bond (Ø2mm, length 50cm)	
27050	<b>HMI Fresnel 1.2kW 220-240V</b> <span style="float: right;"><b>0 zł</b></span>	
		<b>Head fitted w/</b> Fresnel lens Ø175mm, 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1½") spigot
		<b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm
<b>Additional</b>		
42102	HMI/MSR (Osram/Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K	
25030	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection	
25030DMX	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control	
25230	Magnetic ballast BCS-1.2kW/E (220-240V, 50Hz, 7-pin Veam® type female connector)	
<i>Magnetic ballast w/ DMX control on request only</i>		
28853	Adapter cable for use w/ other brand 1.2kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 1.2kW)	
28203	8m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)	
28204	15m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)	
28859	Gel frame Ø258mm	
28304	Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm)	
28850	Cone w/ variable aperture Ø269mm	
28050	4-leaf rotating barndoor Ø269mm	
28857	8-leaf rotating barndoor Ø269mm	
5360.170	Spare manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1½") spigot (for HMI Fresnel 1.2kW)	
82013	Hook clamp w/ 28mm (1½") socket	
28151	Accessory safety bond (Ø2mm, length 50cm)	

27060	<b>HMI Fresnel 2.5kW 220-240V</b> <b>Head fitted w/</b> Fresnel lens Ø250mm, 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1½") spigot <b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø323mm + 4-leaf rotating barndoor Ø323mm
<b>Additional</b>	
42103	HMI/MSR (Osram/Philips®) high-efficiency SE HR 2500W lamp (G38 base) 6000K
25040	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection
25040DMX	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control
25050	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors)
25050DMX	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control
25240	Magnetic ballast BCS-2.5kW/E (220-240V, 50Hz, 7-pin Veam® type female connector)
<i>Magnetic ballast w/ DMX control on request only</i>	
28863	Adapter cable for use w/ other brand 2.5kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 2.5kW & Par 4/2.5kW)
28205	8m head to ballast extension cable (for HMI Fresnel 2.5kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)
28206	15m head to ballast extension cable (for HMI Fresnel 2.5kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)
28093	Gel frame Ø323mm
28306	Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)
28090	Cone small aperture Ø323mm
28091	Cone medium aperture Ø323mm
28092	Cone large aperture Ø323mm
28114	4-leaf rotating barndoor Ø323mm
28071	8-leaf rotating barndoor Ø323mm
5370.170	Spare manual "U"-shape flat base stirrup w/ dual lock-off knobs and 28mm (1½") spigot (for HMI Fresnel 2.5kW)
82013	Hook clamp w/ 28mm (1½") socket
28150	Accessory safety bond (Ø2mm, length 70cm)
<b>HMI Fresnel 4kW 220-240V</b>	
27070	<b>Head fitted w/</b> Fresnel lens Ø300mm, 0.8m length cable w/ 9-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot <b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ 9-pin male and female bayonet Veam® type connectors + adaptor cable 4kW/2.5kW + gel frame Ø408mm + 4-leaf rotating barndoor Ø401mm
<b>Additional</b>	
42104	HMI/MSR (Osram/Philips®) high-efficiency SE HR 4000W lamp (G38 base) 6000K
25050	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors)
25050DMX	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control
25060	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors)
25060DMX	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control
25250	Magnetic ballast BCS-4kW/E (220-240V, 50Hz, 9-pin Veam® type female connector)
<i>Magnetic ballast w/ DMX control on request only</i>	
28873	Adapter cable for use w/ other brand 4kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 4kW & Par 4/2.5kW)
28207	8m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products)
28208	15m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products)
28097	Gel frame Ø408mm
28307	Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm)
28094	Cone small aperture Ø401mm
28095	Cone small medium Ø401mm
28096	Cone large aperture Ø401mm
28115	4-leaf rotating barndoor Ø401mm
28075	8-leaf rotating barndoor Ø401mm
82013	Hook clamp w/ 28mm (1½") socket
82002	Safety cable 50kg (Ø4mm, length 70cm)

27081	<b>HMI Fresnel 6kW Compact 220-240V</b> <b>Head fitted w/</b> Proprietary Fresnel lens Ø450mm, 0.8m length cable w/ 16-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1 1/8") socket <b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + gel frame Ø546mm + 4-leaf rotating barndoor Ø546mm
<b>Additional</b>	
42206	HMI/MSR (Osram/Philips®) high-efficiency SE HR 6000W lamp (GY38 base) 6000K
25060	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors)
25060DMX	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control
25070	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors)
25070DMX	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control
25260	Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector)
25260DMX	Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) w/ DMX control
28883	Adapter cable for use w/ other brand 6kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 6kW Compact)
28209	8m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (not for 120V products)
28210	1.5m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (for both 230V & 120V use)
28889	Gel frame Ø546mm
28884	Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm)
28886	4-leaf rotating barndoor Ø546mm
28887	8-leaf rotating barndoor Ø546mm
82013	Hook clamp w/ 28mm (1 1/8") socket
82002	Safety cable 50kg (Ø4mm, length 70cm)

## QuartzColor HMI Pars

For HMI Par **PO** versions, please contact us

27520	<b>HMI Par 200W 220-240V</b> <b>Head fitted w/</b> 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 16mm (5/8") socket <b>Supplied w/</b> 7m length head to ballast extension cable fitted w/ 7-pin male and female Amphenol® twist lock connectors + gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm + diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø146mm; & frosted Fresnel Ø150mm) + lens carrying case
27521	<b>HMI Par 200W 220-240V + ballast - SET</b> <b>Head fitted w/</b> 0.8m length cable w/ 7-pin Amphenol® male twist lock connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 16mm (5/8") socket <b>Supplied w/</b> electronic ballast 200W (7-pin Amphenol® female connector) + 7m length head to ballast extension cable fitted w/ 7-pin male and female Amphenol® twist lock connectors + gel frame Ø168mm + scrim set 4 pieces (full single + full double + half single + half double; Ø168mm) + diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø146mm; & frosted Fresnel Ø150mm) + 4-leaf rotating barndoor Ø168mm + plywood flight case
<b>Additional</b>	
42201	HMI/MSR (Osram/Philips®) SE HR 200W lamp (GZY9.5 base) 6000K
25921	Electronic ballast 200W (110/220V, 50/60Hz, 7-pin Amphenol® female connector) w/ auto voltage selection <i>HMI Par 200W can be used w/ other brand 200W ballast without additional adapter cable</i>
28823	7m head to ballast extension cable (for HMI Fresnel & Par 200W) fitted w/ 7-pin male and female Amphenol® twist lock connectors (not for 120V products)
28047	Gel frame Ø168mm
28309	Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm)
28048	4-leaf rotating barndoor Ø168mm
28837	8-leaf rotating barndoor Ø168mm
28838NS	Mounted spot proprietary lens Ø146mm, black handle
28838MF	Mounted medium flood proprietary lens Ø146mm, green handle
28838WF	Mounted wide flood proprietary lens Ø1465mm, yellow handle
28838EW	Mounted extra-wide flood proprietary lens Ø146mm, red handle
28838FF	Mounted frosted Fresnel proprietary lens Ø150mm, white handle
28828	Diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø146mm; & frosted Fresnel Ø150mm)

28811	Carrying case for 5 lenses up to Ø205mm (for HMI Par 200 & 575W, OneLight™ HMI Par 200 & 575W); 28 x 34 x 28cm (ext. dim. L x W x H) weight (empty) 4.5kg
28804	Complete diffusion proprietary lens set w/ carrying case (28828 + 28811)
82013	Hook clamp w/ 28mm (1½") socket
28152	Accessory safety bond (Ø2mm, length 40cm)
27540	<p><b>HMI Par 575W 220-240V</b></p> <p><b>Head fitted w/</b> 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 28mm (1½") spigot</p> <p><b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø229mm + 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; &amp; frosted Fresnel Ø200mm) + lens carrying case</p>
27541	<p><b>HMI Par 575W 220-240V + ballast - SET</b></p> <p><b>Head fitted w/</b> 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape stirrup w/ single lock-off knob and 28mm (1½") spigot</p> <p><b>Supplied w/</b> <u>electronic ballast 575W</u> (7-pin Veam® type female connector) + 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + gel frame Ø229mm + <u>scrim set 4 pieces</u> (full single + full double + half single + half double; Ø229mm) + 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; &amp; frosted Fresnel Ø200mm) + lens carrying case</p>
<b>Additional</b>	
42101	HMI/MSR (Osram/Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K
25941	Electronic ballast 575W (110/220V, 50/60Hz, 7-pin Veam® type female connector) w/ auto voltage selection
25030	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection
25030DMX	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control
25220	Magnetic ballast BCS-575W/E (220-240V, 50Hz, 7-pin Veam® type female connector)
<i>Magnetic ballast w/ DMX control on request only</i>	
28843	Adapter cable for use w/ other brand 575W ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 575W)
28201	8m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)
28202	15m head to ballast extension cable (for HMI Fresnel & Par 575W) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)
28086	Gel frame Ø229mm
28305	Scrim set 4 pieces (full single + full double + half single + half double; Ø229mm)
28110	4-leaf rotating barndoor Ø230mm
28111	8-leaf rotating barndoor Ø230mm
28838NS	Mounted spot lens Ø205mm, black handle
28838MF	Mounted medium flood lens Ø205mm, green handle
28838WF	Mounted wide flood lens Ø205mm, yellow handle
28838EW	Mounted extra-wide flood lens Ø205mm, red handle
28838FF	Mounted frosted Fresnel lens Ø200mm, white handle
28838	Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm)
28811	Carrying case for 5 lenses up to Ø205mm (for HMI Par 200 & 575W, OneLight™ HMI Par 200 & 575W); 28 x 34 x 28cm (ext. dim. L x W x H) weight (empty) 4.5kg
28805	Complete diffusion lens set Ø200/205mm w/ carrying case (28838 + 28811)
82013	Hook clamp w/ 28mm (1½") socket
28152	Accessory safety bond (Ø2mm, length 40cm)
27550	<p><b>HMI Par 1.2kW 220V</b></p> <p><b>Head fitted w/</b> 0.8m length cable w/ 7-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot</p> <p><b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ 7-pin male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø323mm + diffusion proprietary lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel: Ø250mm) + lens carrying case</p>

## Additional

42102	HMI/MSR (Osram/Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K
25030	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection
25030DMX	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control
25040	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection
25040DMX	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control
25230	Magnetic ballast BCS-1.2kW/E (220-240V, 50Hz, 7-pin Veam® type female connector)
<i>Magnetic ballast w/ DMX control on request only</i>	
28853	Adapter cable for use w/ other brand 1.2kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 1.2kW)
28203	8m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)
28204	15m head to ballast extension cable (for HMI Fresnel & Par 1.2kW) fitted w/ 7-pin male and female bayonet Veam® type connectors (not for 120V products)
28093	Gel frame Ø323mm
28306	Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)
28114	4-leaf rotating barndoor Ø323mm
28071	8-leaf rotating barndoor Ø323mm
28341	Mounted spot <b>proprietary</b> lens Ø250mm, black handle
28342	Mounted medium flood <b>proprietary</b> lens Ø250mm, green handle
28343	Mounted wide flood <b>proprietary</b> lens Ø250mm, yellow handle
28344	Mounted extra-wide flood <b>proprietary</b> lens Ø250mm, red handle
28345	Mounted frosted Fresnel <b>proprietary</b> lens Ø250mm, white handle
28848	Diffusion <b>proprietary</b> lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm)
28814	Carrying case for 5 lenses Ø250mm (for HMI Par 1.2kW, OneLight™ HMI Par 1.2kW & Tungsten Par 1kW); 38 x 43 x 42cm (ext. dim. L x W x H) weight (empty) 7kg
28806	Complete diffusion <b>proprietary</b> lens set Ø250mm w/ carrying case (28848 + 28814)
82013	Hook clamp w/ 28mm (1½") socket
82002	Safety cable 50kg (Ø4mm, length 70cm)

27570

### HMI Par 4/2.5kW 220-240V

**Head fitted w/** 0.8m length cable w/ 9-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot

**Supplied w/** 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø401mm + diffusion **proprietary** lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø350mm) + lens carrying case + adapter cable for use w/ 2.5kW ballast

## Additional

42103	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>2500W</b> lamp (G38 base) 6000K
42104	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>4000W</b> lamp (G38 base) 6000K
25040	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection
25040DMX	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control
25050	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors)
25050DMX	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control
25240	Magnetic ballast BCS-2.5kW/E (220-240V, 50Hz, 7-pin Veam® type female connector)
25250	Magnetic ballast BCS-4kW/E (220-240V, 50Hz, 9-pin Veam® type female connector)
<i>Magnetic ballasts w/ DMX control on request only</i>	
28032	Adaptor cable for 2.5kW use, fitted w/ 9-pin male and female bayonet Veam® type connectors (for HMI Par 4/2.5kW)
28863	Adapter cable for use w/ other brand 2.5kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 2.5kW & Par 4/2.5kW)
28873	Adapter cable for use w/ other brand 4kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel 4kW & Par 4/2.5kW)
28207	8m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products)
28208	15m head to ballast extension cable (for HMI Fresnel 4kW & Par 4/2.5kW) fitted w/ 9-pin male and female bayonet Veam® type connectors (not for 120V products)
28097	Gel frame Ø408mm
28307	Scrim set 4 pieces (full single + full double + half single + half double; Ø408mm)
28115	4-leaf rotating barndoor Ø401mm
28075	8-leaf rotating barndoor Ø401mm
28441	Mounted spot <b>proprietary</b> lens Ø350mm, black handle
28442	Mounted medium flood <b>proprietary</b> lens Ø350mm, green handle

28443	Mounted wide flood <b>proprietary</b> lens Ø350mm, yellow handle
28444	Mounted extra-wide flood <b>proprietary</b> lens Ø350mm, red handle
28445	Mounted frosted Fresnel <b>proprietary</b> lens Ø350mm, white handle
28868	Diffusion <b>proprietary</b> lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø350mm)
28812	Carrying case for 5 lenses Ø350mm (for HMI Par 4/2.5kW & Tungsten Par 2kW); 48 x 39 x 49cm (ext. dim. L x W x H), weight (empty) 11kg
28808	Complete diffusion <b>proprietary</b> lens set Ø350mm w/ carrying case (28868 + 28812)
82013	Hook clamp w/ 28mm (1½") socket
82002	Safety cable 50kg (Ø4mm, length 70cm)
27588	<b>HMI Par 6kW Compact 220-240V</b> <b>Head fitted w/</b> 0.8m length cable w/ 16-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot  <b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø546mm + diffusion <b>proprietary</b> lens set 5 pieces (full single + full double + half single + half double + frosted Fresnel; Ø450mm) + lens carrying case
<b>Additional</b>	
42206	HMI/MSR (Osram/Philips®) high-efficiency SE HR 6000W lamp (GY38 base) 6000K
25060	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors)
25060DMX	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control
25070	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors)
25070DMX	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control
25260	Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector)
25260DMX	Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) w/ DMX control
28883	Adapter cable for use w/ other brand 6kW ballast (to be specified when ordering) 25cm length (for HMI Fresnel & Par 6kW Compact)
28209	8m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (not for 120V products)
28210	15m head to ballast extension cable (for HMI Fresnel & Par 6kW Compact) fitted w/ 16-pin male and female bayonet Veam® type connectors (for both 230V & 120V use)
28889	Gel frame Ø546mm
28884	Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm)
28886	4-leaf rotating barndoor Ø546mm
28887	8-leaf rotating barndoor Ø546mm
28541	Mounted spot <b>proprietary</b> lens Ø450mm, black handle
28542	Mounted medium flood <b>proprietary</b> lens Ø450mm, green handle
28543	Mounted wide flood <b>proprietary</b> lens Ø450mm, yellow handle
28544	Mounted extra-wide flood <b>proprietary</b> lens Ø450mm, red handle
28545	Mounted frosted Fresnel <b>proprietary</b> lens Ø450mm, white handle
28888	Diffusion <b>proprietary</b> lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm)
28813	Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg
28810	Complete diffusion <b>proprietary</b> lens set Ø450mm w/ carrying case (28888 + 28813)
82013	Hook clamp w/ 28mm (1½") socket
82002	Safety cable 50kg (Ø4mm, length 70cm)
27590	<b>HMI Par 12/6kW 220-240V</b> <b>Head fitted w/</b> 0.8m length cable w/ 8-pin in-line bayonet Veam® type male connector, On/off switching by double push buttons on the rear of the unit, full bottom skid, manual "U"-shape square base stirrup w/ dual lock-off knobs and 28mm (1½") spigot  <b>Supplied w/</b> 8m length head to ballast extension cable fitted w/ male and female bayonet Veam® type connectors + 4-leaf rotating barndoor Ø546mm + Diffusion <b>proprietary</b> lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm) + lens carrying case
<b>Additional</b>	
42206	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>6000W</b> lamp (GY38 base) 6000K
42212	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>12000W</b> lamp (GY38 base) 6000K
25060	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors)
25060DMX	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control
25070	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors)
25070DMX	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control

25260	Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector)
25260DMX	Magnetic ballast BCS-6kW/E (208-240V, 50/60Hz, 16-pin Veam® type female connector) w/ DMX control
25270	Magnetic ballast BCS-12kW/E (220-240V, 50Hz, 8-pin Veam® type female connector)
<i>Magnetic ballast w/ DMX control on request only</i>	
28894	Adaptor cable for 6kW use, fitted w/ 8-pin male and female bayonet Veam® type connectors
28896	Adapter cable for use w/ other brand 12/6kW ballast (to be specified when ordering) 25cm length (for HMI Par 12/6kW)
28211	8m head to ballast extension cable (for HMI Par 12/6kW) fitted w/ 8-pin male and female bayonet Veam® type connectors (not for 120V products)
28212	15m head to ballast extension cable (for HMI Par 12/6kW) fitted w/ 8-pin male and female bayonet Veam® type connectors (not for 120V products)
28889	Gel frame Ø546mm
28884	Scrim set 4 pieces (full single + full double + half single + half double; Ø546mm)
28886	4-leaf rotating barndoor Ø546mm
28887	8-leaf rotating barndoor Ø546mm
28541	Mounted spot <b>proprietary</b> lens Ø450mm, black handle
28542	Mounted medium flood <b>proprietary</b> lens Ø450mm, green handle
28543	Mounted wide flood <b>proprietary</b> lens Ø450mm, yellow handle
28544	Mounted extra-wide flood <b>proprietary</b> lens Ø450mm, red handle
28545	Mounted frosted Fresnel <b>proprietary</b> lens Ø450mm, white handle
28888	Diffusion <b>proprietary</b> lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø450mm)
28813	Carrying case for 5 lenses Ø450mm (for Tungsten Par 5kW & 10kW, HMI Par 6kW Compact & 12/6kW); 62 x 42 x 62cm (ext. dim. L x W x H), weight (empty) 14.5kg
28810	Complete diffusion lens set Ø450mm w/ carrying case (28888 + 28813)
82013	Hook clamp w/ 28mm (1 1/8") socket
82002	Safety cable 50kg (Ø4mm, length 70cm)

## Daylight compact spotlights

# QuartzColor OneLight™ HMI Fresnels

27044	<p><b>OneLight™ HMI Fresnel 575W 90-260V</b></p> <p><b>Unit supplied w/ integrated High Frequency</b> electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø130mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K</p>
27044DMX	<p><b>OneLight™ HMI Fresnel 575W 90-260V DMX</b></p> <p><b>Unit supplied w/ integrated High Frequency</b> electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø130mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, <b>DMX card</b>, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot</p> <p><b>Supplied w/</b> gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K</p> <p><b>Additional</b></p>
42108	MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base, medium bi-post) 6000K
27044EB	<i>Spare</i> High Frequency electronic ballast 575W (90-260V, 50/60Hz, for OneLight™ 575W Fresnel)
28900	DMX card for OneLight™ Fresnels & Pars
28849	Gel frame Ø198mm
28844	Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm)
28840	Cone w/ variable aperture Ø200mm
28846	4-leaf rotating barndoor Ø200mm
28847	8-leaf rotating barndoor Ø200mm
82013	Hook clamp w/ 28mm (1 1/8") socket
28151	Accessory safety bond (Ø2mm, length 50cm)
27054	<p><b>OneLight™ HMI Fresnel 1.2kW 90-260V</b></p>

**Unit supplied w/ integrated High Frequency** electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø175mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") spigot

**Supplied w/** gel frame Ø258mm and 4-leaf rotating barndoor Ø269mm + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

27054DMX

### OneLight™ HMI Fresnel 1.2kW 90-260v DMX

**Unit supplied w/ integrated High Frequency** electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), Fresnel lens Ø175mm, 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, DMX card, full bottom skid, manual "U"-shape flat base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") spigot

**Supplied w/** gel frame Ø258mm + 4-leaf rotating barndoor Ø269mm + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

#### Additional

42203

MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K

27054EB

*Spare* High Frequency electronic ballast 1.2kW (90-260V, 50/60Hz, for OneLight™ 1.2kW Fresnel)

28900

DMX card for OneLight™ Fresnels & Pars

28859

Gel frame Ø258mm

28304

Scrim set 4 pieces (full single + full double + half single + half double; Ø258mm)

28850

Cone w/ variable aperture Ø269mm

28050

4-leaf rotating barndoor Ø269mm

28857

8-leaf rotating barndoor Ø269mm

82013

Hook clamp w/ 28mm (1 1/8") socket

28151

Accessory safety bond (Ø2mm, length 50cm)

## QuartzColor OneLight™ HMI Pars

27544E

### OneLight™ HMI Par 575W 90-260v w/o lens system

**Unit supplied w/ integrated High Frequency** electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot

**Supplied w/** 4-leaf rotating barndoor Ø230mm + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K

27544

### OneLight™ HMI Par 575W 90-260v

**Unit supplied w/ integrated High Frequency** electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot

**Supplied w/** 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) + lens carrying case + MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K

27544DMX

### OneLight™ HMI Par 575W 90-260v DMX

**Unit supplied w/ integrated High Frequency** electronic ballast 575W w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, DMX card, full bottom skid, manual "U"-shape flat base stirrup w/ single "L"-shape lock-off knob and 28mm (1 1/8") spigot

**Supplied w/** 4-leaf rotating barndoor Ø230mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm) + lens carrying case MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base) 6000K

#### Additional

42108

MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base, medium bi-post) 6000K

27544EB

*Spare* High Frequency electronic ballast 575W (90-260V, 50/60Hz, for OneLight™ 575W Par)

28900

DMX card for OneLight™ Fresnels & Pars

28086

Gel frame Ø229mm

28305

Scrim set 4 pieces (full single + full double + half single + half double; Ø229mm)

28110

4-leaf rotating barndoor Ø230mm

28111

8-leaf rotating barndoor Ø230mm

28838NS

Mounted spot lens Ø205mm, black handle

28838MF

Mounted medium flood lens Ø205mm, green handle

28838WF

Mounted wide flood lens Ø205mm, yellow handle

28838EW

Mounted extra-wide flood lens Ø205mm, red handle



28838FF	Mounted frosted Fresnel lens Ø200mm, white handle
28838	Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm)
28811	Carrying case for 5 lenses up to Ø205mm (for HMI Par 200 & 575W, OneLight™ HMI Par 200 & 575W); 28 x 34 x 28cm (ext dim L x W x H) weight (empty) 4.5kg
28805	Complete diffusion lens set Ø200/205mm w/ carrying case (28838 + 28811)
28838NSS	Mounted spot lens Ø205mm, black handle, w/ anti light-spill ring
28838MFS	Mounted medium flood lens Ø205mm, green handle, w/ anti light-spill ring
28838WFS	Mounted wide flood lens Ø205mm, yellow handle, w/ anti light-spill ring
28838EWS	Mounted extra-wide flood lens Ø205mm, red handle, w/ anti light-spill ring
28838FFS	Mounted frosted Fresnel lens Ø200mm, white handle, w/ anti light-spill ring
28838SPR	Diffusion lens set 5 pieces w/ anti light-spill ring (spot + medium flood + wide flood + extra-wide flood; Ø205mm; & frosted Fresnel Ø200mm)
28805SPR	Complete diffusion lens set Ø200/205mm w/ anti light-spill ring and carrying case (28838SPR + 28811)
82013	Hook clamp w/ 28mm (1 1/8") socket
28152	Accessory safety bond (Ø2mm, length 40cm)

27554E

**OneLight™ HMI Par 1.2kW 90-260V w/o lens system**

**Unit supplied w/ integrated High Frequency** electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape square base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") socket

**Supplied w/** 4-leaf rotating barndoor Ø323mm + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

27554

**OneLight™ HMI Par 1.2kW 90-260V**

**Unit supplied w/ integrated High Frequency** electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, full bottom skid, manual "U"-shape square base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") socket

**Supplied w/** 4-leaf rotating barndoor Ø323mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm) + lens carrying case + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

27554DMX

**OneLight™ HMI Par 1.2kW 90-260V DMX**

**Unit supplied w/ integrated High Frequency** electronic ballast 1.2kW w/ Cleararc® technology, universal power supply (90-260V, 50/60Hz), 3m length bare ended cable, local On/Off power switch, On/Off fan power switch, 100~50% dimming control knob, DMX card, full bottom skid, manual "U"-shape square base stirrup w/ dual "L"-shape lock-off knobs and 28mm (1 1/8") socket

**Supplied w/** 4-leaf rotating barndoor Ø323mm + diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm) + lens carrying case + MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base) 6000K

**Additional**

42203

MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K

27554EB

Spare High Frequency electronic ballast 1.2kW (90-260V, 50/60Hz, for OneLight™ 1.2kW Par)

28900

DMX card for OneLight™ Fresnels &amp; Pars

28093

Gel frame Ø323mm

28306

Scrim set 4 pieces (full single + full double + half single + half double; Ø320mm)

28114

4-leaf rotating barndoor Ø323mm

28071

8-leaf rotating barndoor Ø323mm

28341

Mounted spot lens Ø250mm, black handle

28342

Mounted medium flood lens Ø250mm, green handle

28343

Mounted wide flood lens Ø250mm, yellow handle

28344

Mounted extra-wide flood lens Ø250mm, red handle

28345

Mounted frosted Fresnel lens Ø250mm, white handle

28848

Diffusion lens set 5 pieces (spot + medium flood + wide flood + extra-wide flood + frosted Fresnel; Ø250mm)

28814

Carrying case for 5 lenses Ø250mm (for HMI Par 1.2kW, OneLight™ HMI Par 1.2kW & Tungsten Par 1kW);  
38 x 43 x 42cm (ext dim L x W x H) weight (empty) 7kg

28806

Complete diffusion lens set Ø250mm w/ carrying case (28848 + 28814)

*Diffusion lens w/ anti light-spill ring on request*

82013

Hook clamp w/ 28mm (1 1/8") socket

82002

Safety cable 50kg (Ø4mm, length 70cm)

## QuartzColor Ceramic Fresnels

27018

**Ceramic Fresnel DM 150W 220-240V 4200K+3000K**

**Unit supplied w/ integrated** electronic ballast 150W & 220~240V/50Hz power supply, On/Off in-line toggle switch 8A/250V, 4.5m length bare ended cable, Fresnel lens Ø130mm, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") socket  
**Supplied w/** gel frame Ø168mm + 4-leaf rotating barndoor Ø168mm + Philips® Mastercolor CDM 150W SA/T 150/942 4200K and CDM 150W SA/T 150/830 3000K lamps

#### Additional

42926	Mastercolor CDM (Philips®) SE 150W SA/T 150/942 lamp (G12 base) <b>4200K</b>
42207	Mastercolor CDM (Philips®) SE 150W SA/T 150/830 lamp (G12 base) <b>3000K</b>
5315/1	<i>Spare</i> High Frequency electronic ballast 150W (220-240V, 50Hz, for Ceramic Fresnel DM 150W)
28047	Gel frame Ø168mm
28309	Scrim set 4 pieces (full single + full double + half single + half double; Ø168mm)
28049	Cone w/ variable aperture Ø168mm
28048	4-leaf rotating barndoor Ø168mm
28837	8-leaf rotating barndoor Ø168mm
82013	Hook clamp w/ 28mm (1½") socket
28152	Accessory safety bond (Ø2mm, length 40cm)

27028 **Ceramic Fresnel 250W 90-265V 6000K+3200K**  
**Unit supplied w/ integrated** electronic ballast 250W & universal voltage (90-265V, 50/60Hz), local On/Off power switch, 5m length bare ended cable, Fresnel lens Ø130mm, full bottom skid, manual "U"-shape flat base stirrup w/ single lock-off knob and 28mm (1½") socket  
**Supplied w/** gel frame Ø198mm + 4-leaf rotating barndoor Ø200mm + Philips® Ceramic MSR 250W SE HR 6000K and Ceramic ST 250W SE HR 3200K lamps

#### Additional

42250	Ceramic MSR (Philips®) SE HR 250W lamp (GZY9.5 base) <b>6000K</b>
5325/1	Ceramic ST (Philips®) SE HR 250W lamp (GZY9.5 base) <b>3200K</b>
5325/25	<i>Spare</i> High Frequency electronic ballast 250W (90-265V, 50/60Hz, ballast + igniter, for Ceramic Fresnel 250W)
28849	Gel frame Ø198mm
28844	Scrim set 4 pieces (full single + full double + half single + half double; Ø198mm)
28840	Cone w/ variable aperture Ø200mm
28846	4-leaf rotating barndoor Ø200mm
28847	8-leaf rotating barndoor Ø200mm
82013	Hook clamp w/ 28mm (1½") socket
28151	Accessory safety bond (Ø2mm, length 50cm)

## Miscellaneous

### QuartzColor ballasts for HMI

#### Electronic ballasts 110/220V or more, see below

25921	Electronic ballast 200W (110/220V, 50/60Hz, 7-pin Amphenol® female connector) w/ auto voltage selection
25932	Electronic ballast 575/400W (110/220V, 50/60Hz, 7-pin Schaltbau® & 7-pin Amphenol® female connectors) w/ auto voltage selection
25941	Electronic ballast 575W (110/220V, 50/60Hz, 7-pin Veam® type female connector) w/ auto voltage selection
25030	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection
25030DMX	Electronic ballast 1.2kW/575W (110/220V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control
25040	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection
25040DMX	Electronic ballast 2.5/1.2kW (110/230V, 50/60Hz, 7-pin Veam® type female connectors) w/ auto voltage selection and DMX control
25440	Electronic ballast 2.5/1.2kW (190-250V, 50/60Hz, 7-pin Veam® type female connectors) w/ dual socket autoselecting
25440DMX	Electronic ballast 2.5/1.2kW (190-250V, 50/60Hz, 7-pin Veam® type female connectors) w/ dual socket autoselecting and DMX control
25050	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors)
25050DMX	Electronic ballast 4/2.5kW (95-260V, 50/60Hz, 7-pin & 9-pin Veam® type female connectors) w/ DMX control
25060	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors)
25060DMX	Electronic ballast 6/4kW (195-260V, 50/60Hz, 9-pin & 16-pin Veam® type female connectors) w/ DMX control

25070	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors)
25070DMX	Electronic ballast 12/6kW (195-260V, 50/60Hz, 16-pin & 8-pin Veam® type female connectors) w/ DMX control

*For the Power Factor of each model, please refer in corresponding data sheet*

### **Magnetic ballasts 220-240V** except 6kW, see below

25220	Magnetic ballast BCS-575W/E (220-240V, 50Hz, 7-pin Veam® type female connector)
25230	Magnetic ballast BCS-1.2kW/E (220-240V, 50Hz, 7-pin Veam® type female connector)
25240	Magnetic ballast BCS-2.5kW/E (220-240V, 50Hz, 7-pin Veam® type female connector)
25250	Magnetic ballast BCS-4kW/E (220-240V, 50Hz, 9-pin Veam® type female connector)
25260	Magnetic ballast BCS-6kW/E ( <b>208</b> -240V, 50/ <b>60</b> Hz, 16-pin Veam® type female connector)
25260DMX	Magnetic ballast BCS-6kW/E ( <b>208</b> -240V, 50/ <b>60</b> Hz, 16-pin Veam® type female connector) w/ DMX control
25270	Magnetic ballast BCS-12kW/E (220-240V, 50Hz, 8-pin Veam® type female connector)

*Other magnetic ballast w/ DMX control on request only*

## Lamps

### **Incandescent lamps, screw type**

Incandescent (Argaphoto) lamp type P2/1 500W 230V (E27 base)
Incandescent (Argaphoto) lamp type P2/1 500W 240V (E27 base)

### **Tungsten halogen SE (single ended) lamps, 2-pin**

Tungsten halogen SE lamp type CP81 (FMF) 300W 230V (GY9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type CP81 (FSK) 300W 240V (GY9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type CP82 (FRH) <b>500W</b> 230V (GY9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type CP82 (FRJ) 500W 240V (GY9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type A1/233 (DYR) <b>650W</b> 230V (GZ9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type A1/233 (DYR) 650W 240V (GZ9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type CP89 (FRL) 650W 230V (GY9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type CP89 (FRM) 650W 240V (GY9.5 base, oriented 2-pin) 3200K
Tungsten halogen SE lamp type CP40 (FKJ) <b>1000W</b> 230V (G22 base, medium bi-post) 3200K
Tungsten halogen SE lamp type CP40 (FKJ) 1000W 240V (G22 base, medium bi-post) 3200K
Tungsten halogen SE lamp type CP41 (FKK) <b>2000W</b> 230V (G38 base, mogul bi-post) 3200K
Tungsten halogen SE lamp type CP41 (FKK) 2000W 240V (G38 base, mogul bi-post) 3200K
Tungsten halogen SE lamp type CP29 <b>5000W</b> 230V (G38 base, mogul bi-post) 3200K
Tungsten halogen SE lamp type CP29 5000W 240V (G38 base, mogul bi-post) 3200K
Tungsten halogen SE lamp type CP83 <b>10000W</b> 230V (G38 base, mogul bi-post) 3200K
Tungsten halogen SE lamp type CP83 10000W 240V (G38 base, mogul bi-post) 3200K

## Tungsten halogen SE (single ended) lamps twin filament, 4-pin

	Tungsten halogen SE twin filament lamp type CP30 <b>1250/1250W</b> 230V (GX38q base) 3200K
	Tungsten halogen SE twin filament lamp type CP30 1250/1250W 240V (GX38q base) 3200K
	Tungsten halogen SE twin filament lamp type CP58 1250/2500W 230V (GX38q base) 3200K
	Tungsten halogen SE twin filament lamp type CP58 1250/2500W 240V (GX38q base) 3200K
	Tungsten halogen SE twin filament lamp type CP32 <b>2500/2500W</b> 230V (GX38q base) 3200K
	Tungsten halogen SE twin filament lamp type CP32 2500/2500W 240V (GX38q base) 3200K

## Tungsten halogen DE (double ended) lamps, R7s base

	Tungsten halogen DE linear lamp type K9 <b>300W</b> 230V (R7s base, MOL 119mm) 3200K
	Tungsten halogen DE linear lamp type K1 <b>500W</b> 230V (R7s base, MOL 119mm) 3200K
	Tungsten halogen DE linear lamp type K1 500W 240V (R7s base, MOL 119mm) 3200K
	Tungsten halogen DE linear lamp type P2/10 <b>625W</b> 230V (R7s base, MOL 189.1mm) 3200K
	Tungsten halogen DE linear lamp type P2/10 625W 240V (R7s base, MOL 189.1mm) 3200K
	Tungsten halogen DE linear lamp type P2/13 (DXX) <b>800W</b> 230V (R7s base, MOL 79.4mm) 3200K
	Tungsten halogen DE linear lamp type P2/13 (DXX) 800W 240V (R7s base, MOL 79.4mm) 3200K
	Tungsten halogen DE linear lamp type P2/11 (EME) 800W 230V (R7s base, MOL 119mm) 3200K
	Tungsten halogen DE linear lamp type P2/11 (EME) 800W 240V (R7s base, MOL 119mm) 3200K
	Tungsten halogen DE linear lamp type P2/7 (EKM) <b>1000W</b> 230V (R7s base, MOL 189.1mm) 3200K
	Tungsten halogen DE linear lamp type P2/7 (EKM) 1000W 240V (R7s base, MOL 189.1mm) 3200K
	Tungsten halogen DE linear lamp type P2/20 1000W 230V (R7s base, MOL 119mm) 3200K
	Tungsten halogen DE linear lamp type P2/20 1000W 240V (R7s base, MOL 119mm) 3200K
	Tungsten halogen DE linear lamp type P2/35 1000W 230V (R7s base, MOL 95.3mm) 3200K
	Tungsten halogen DE linear lamp type P2/35 1000W 240V (R7s base, MOL 95.3mm) 3200K
	Tungsten halogen DE linear lamp type P2/12 <b>1250W</b> 230V (R7s base, MOL 189.1mm) 3200K
	Tungsten halogen DE linear lamp type P2/12 1250W 240V (R7s base, MOL 189.1mm) 3200K
	Tungsten halogen DE linear lamp type P2/27 (FEX) <b>2000W</b> 230V (R7s base, MOL 143.8mm) 3200K
	Tungsten halogen DE linear lamp type P2/27 (FEX) 2000W 240V (R7s base, MOL 143.8mm) 3200K

## Daylight metal halide SE (single ended) HR (hot restrike) lamps

42201	HMI/MSR (Osram/Philips®) SE HR <b>200W</b> lamp (GZY9.5 base) 6000K
42200	HMI/MSR (Osram/Philips®) SE HR <b>400W</b> lamp (GZY9.5 base) 6000K
42101	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>575W</b> lamp (G22 base) 6000K
42108	MSR (Philips®) high-efficiency SE HR 575W lamp (G22 base, medium bi-post) 6000K
42102	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>1200W</b> lamp (G38 base, mogul bi-post) 6000K
42203	MSR (Philips®) high-efficiency SE HR 1200W lamp (G38 base, mogul bi-post) 6000K
42103	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>2500W</b> lamp (G38 base) 6000K
42104	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>4000W</b> lamp (G38 base) 6000K
42206	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>6000W</b> lamp (GY38 base) 6000K
42212	HMI/MSR (Osram/Philips®) high-efficiency SE HR <b>12000W</b> lamp (GY38 base) 6000K

## Ceramic compact discharge SE lamps w/ UV-block

42926	Mastercolor CDM (Philips®) SE <b>150W</b> SA/T 150/942 lamp (G12 base) 4200K
42207	Mastercolor CDM (Philips®) SE 150W SA/T 150/830 lamp (G12 base) 3000K
42250	Ceramic MSR (Philips®) SE HR <b>250W</b> lamp (GZY9.5 base) 6000K
5325/1	Ceramic ST (Philips®) SE HR 250W lamp (GZY9.5 base) 3200K

\* Cennik nie jest ofertą handlową w świetle obowiązujących przepisów kodeksu handlowego.

Firma Milso zastrzega sobie prawo do zmian cen oraz asortymentu.

Nie odpowiada również za błędy w powyższym cenniku.

Cena brutto w zł. zawiera 23% podatku VAT